

# *Ranger Consulting, Inc.*

*Geotechnical, Environmental, Drilling, Construction*

3147 Martha Berry Highway, Rome, Georgia 30165; Phone: 706-290-1782; Fax: 706-290-1701

April 20, 2015

Mr. Tommy Crochet, PE  
McGee Partners, Inc.  
13 Corporate Boulevard  
Suite 200  
Atlanta, GA 30329

RE: Geotechnical Subsurface Exploration, Engineering Evaluation and Dam Visual  
Observation  
Sun Valley Drive Extension  
Roswell, Fulton County, GA

Dear Mr. Crochet:

Ranger Consulting, Inc. (Ranger) is pleased to submit the attached letter report of our geotechnical subsurface exploration and engineering evaluation for the above referenced project. The report of dam visual observations is being submitted under separate cover.

If you have any questions, please contact Sandy Miller or Warren Bailey at 706-290-1782. Ranger appreciates the opportunity to be of service to you on this project.

Sincerely,

A handwritten signature in cursive script, appearing to read "Peggy McGee".

Peggy McGee  
President

Enclosure

**GEOTECHNICAL SUBSURFACE EXPLORATION  
AND ENGINEERING EVALUATION  
Sun Valley Drive Extension  
Roswell, Fulton County, Georgia  
April 20, 2015**

## **INTRODUCTION**

This report provides the results of the geotechnical subsurface exploration and engineering evaluation performed for the Sun Valley Drive Extension project. Included in this report are foundation investigations for the proposed culvert and retaining wall. A dam visual observation letter report is being submitted under separate cover. The property is located in the City of Roswell, Fulton County, Georgia to the east of the existing Sun Valley Drive approximately ¼-mile east of its intersection with Alpharetta Highway and to the north of the existing Warsaw Road Extension. The subsurface conditions of portions of the site were explored by a series of soil borings, and in some locations, rock coring was performed. The results of the borings and a plan showing their approximate location are included with this report. Descriptions of the subsurface conditions encountered in the borings and recommendations for use in designing the culvert and retaining wall foundations are provided. In addition, there is also discussion of the suitability of the soils encountered for use as roadway fill materials and of the rippability of the rock encountered in the rock core borings.

Borings B-1, its offsets and B-7 were performed in a proposed bio-retention area located to the west of the existing creek. Borings B-5, B-6 and B-10 through B-15 were performed in a proposed bio-retention area located to the east of the existing creek. Borings B-2, its offsets, B-3, B-4, B-8 and B-9 were performed around the existing pond in the areas of the proposed littoral shelves. Borings C-1 through C-3 were performed in the area of the proposed culvert. Borings W-1 and W-2 were performed in the area of the proposed retaining wall. The rock cores R-1 through R-10 were performed in both of the proposed bio-retention areas and the areas of the proposed littoral shelves.

## **SITE EXPLORATION PROCEDURES**

Boring locations for B-1 through B-15, C-1 through C-3, W-1, W-2, and HA-1 through HA-4 were established in the field by representatives of McGee Partners, Inc. and AEC, Inc. along with Ranger Consulting, Inc. personnel. In addition, Ranger personnel established the locations for all of the soil boring offsets (B-1A through B-1F and B-2A through B-2D) and rock cores (R-1 through R-10) based on conversations with Mr. Tommy Crochet of McGee Partners, Inc. Boring elevations were then interpolated from the topographic plan provided by McGee Partners, Inc. Consequently, referenced boring locations and elevations should be considered approximate. An all-terrain, rotary drill rig equipped with hollow stem augers was used to advance the boreholes. Representative soil samples were obtained by the Standard Penetration Test. The rock core borings were advanced to rock using NWJ rods and a tri-cone bit. When rock was encountered, an NQWL bit was used to obtain rock cores approximately 1⅞-inches in diameter.

The drill crew prepared field logs as part of the drilling operations. The boring logs included visual classifications of the materials encountered during drilling and the driller's interpretation of the subsurface conditions between samples. The final boring logs included with this report in Appendix III represent the engineer's interpretation of the field logs and additional visual examination of the soil samples. The borings were backfilled with soil cuttings from the drilling process and marked with wooden stakes so that the locations could later be surveyed by another member of the project team.

## **LABORATORY TESTING**

To aid in classifying the soils and determining their engineering properties, laboratory tests were performed on representative soil samples obtained from the soil test borings. All laboratory testing was performed in general accordance with current ASTM standards and included:

- Six (6) GDOT 810 Series (GDT-4, GDT-6, GDT-7) tests on bulk samples from borings B-1 through B-6;
- Three (3) Atterberg Limits (ASTM D4318);
- Three (3) Sieve Analysis with Hydrometer (ASTM D422);
- Three (3) USCS Classification of soils for engineering purposes (ASTM D2487);
- Nine (9) Moisture Content Determinations (ASTM D216);
- One (1) Resistivity; and
- One (1) pH test.

The laboratory test results are summarized in Table 1 of Appendix II and included in Appendix IV.

## **SITE AND SUBSURFACE CONDITIONS**

The project site is geologically sited in a formation composed of biotitic gneiss, mica schist and amphibolite within the Georgia Piedmont Physiographic Region.

### **Soil and Rock Conditions**

The borings drilled generally encountered approximately 1 to 4 inches of topsoil with the thicker topsoil zones encountered on the eastern portion of the site. Fill was encountered in borings B-1, B1-A through B-1F, B-5, B-6, and B-10 through B-14 to depths varying from 2 to 18 feet below the existing ground surface (bgs). The fill encountered in boring B-1 and its offsets was generally described as micaceous sandy silt or silty sand with rock fragments or organic material

consisting of intermixed topsoil and small wood fragments. The fill encountered in borings B-5, B-6, and B-10 through B-14 was generally described as micaceous clayey sand, silty sand, sandy silt or clayey silt with rock fragments or organic material consisting of intermixed topsoil. Standard penetration resistances in the fill soils varied from 6 to over 100 blows per foot (bpf), but may have been amplified by the presence of rock fragments.

Alluvium (water deposited soil) was encountered in borings C-1 through C-3, W-1 and W-2 to depths varying from 3 to 8 feet bgs. The alluvium generally consisted of silty sand, sandy silt, clayey silt, silty clay or sandy clay with organic fragments. Standard penetration resistances in the alluvial soils varied from 0 to 11 bpf, but may have been amplified by the presence of rock fragments.

Residual soils were encountered in most of the borings beneath the topsoil, fill soil or alluvial soils. The residuum was generally described as silty sand or sandy clay with rock fragments. Standard penetration resistances in the residuum varied from 12 to over 100 bpf.

Auger refusal materials are any very hard or very dense material, such as boulders or the upper surface of bedrock, which cannot be penetrated by a power auger. Auger refusal was encountered in all of the borings performed at depths ranging from 2 to 21 feet bgs [approximate elevations ranging from 1051 to 1025 feet above Mean Sea Level (ft-MSL)]. Summaries of the soil boring fill, alluvium, residual and auger refusal depths are included in Tables 2 and 3 of Appendix II.

Rock coring to determine the nature and continuity of refusal materials was performed in rock core borings R-1 through R-10. Rock quality was variable with recovery values (REC) ranging from 71% to 100%, and rock quality designations (RQD) varying from 18% to 71%. Based on visual observations, the rock is typically soft and weathered near the upper surface of the rock; however, rock quality increases with depth. Rock core depths and rock core and proposed ground surface elevations are included as Tables 4 and 5 in Appendix II, and rock core photographs are included as Figure 4 in Appendix I.

All cores listed on the following table are NQ (1 $\frac{7}{8}$ -inches in diameter). REC describes the percent of the rock core run that was recovered. RQD describes the percent of the rock core run that consisted of intact rock core at least 4- inches in length. A summary of the rock core depths and quality are included in Table 3 of Appendix II.

### **Groundwater Conditions**

Groundwater was observed after 24 hours in the culvert borings and wall borings (C-1 through C-3, W-1 and W-2). Stabilized groundwater was encountered at 2 feet bgs (approximate elevations ranging from 1042 to 1040 ft-MSL) in the culvert borings and at depths ranging from 1 to 10 feet bgs (approximate elevation of 1056 ft-MSL) in the wall borings.

Groundwater levels vary with changes in season and rainfall, construction activity, surface water runoff and other site-specific factors. Groundwater levels in the Roswell area are typically lowest in the late summer-early fall and highest in the later winter-early spring; consequently, the water table may vary at times.

Reference should be made to Table 6 in Appendix II for allowable pipe culvert materials based on the laboratory corrosion tests performed on the surface water present in the existing creek.

## **CONCLUSIONS AND RECOMMENDATIONS**

### **Existing Fill Soils**

Based on the GDOT 810 Series testing performed on bulk samples from borings B-1 through B-6, the existing soils to be cut and used as fill in the proposed roadway are Class I-A2 to II-B3 soils. None of these materials should require wasting or removal. Soil moisture content should be maintained within 3 percent of the optimum moisture content. We recommend that the grading contractor have equipment on site during earthwork for both drying and wetting soils. The natural moisture content of the soils from boring B-1 was just over 3 percent of the optimum moisture content, and the natural moisture content of the soils from boring B-2 was more than 6 percent less than the optimum moisture content. Also, fine grained soils including sandy silts were encountered in the proposed cut areas. Establishing subgrades in these fine grained soils may be challenging and could require drying or wetting.

Laboratory testing, including Atterberg Limits, sieve analysis with hydrometer, USCS classification of soils for engineering purposes and moisture content determinations, indicates the residual soils generally encountered just above the underlying rock are silty sands.

For pavement design purposes, Ranger recommends the use of a soil support value of 2.0 based on GDOT county averages. Additionally, a regional factor of 1.8 and a subgrade reaction value,  $k$ , of 110 pounds per cubic inch (pci) are recommended for use in pavement design calculations. We recommend an average soil shrinkage factor of 25 percent for use in earthwork calculations for this project.

### **Quality of Encountered Rock**

Based upon the planned finished grades, rock that requires difficult excavation techniques will be encountered during site grading. Rock cores R-1 through R-10 were performed in both of the proposed bio-retention areas and the areas of the proposed littoral shelves. Based on the rock cores recovered, it appears portions of the encountered rock may be excavated using conventional earth moving equipment such as scrapers, loaders, pans, dozers or graders. The encountered thicknesses of this soft, weathered rock varied from approximately  $\frac{1}{2}$  to  $2\frac{1}{2}$  feet. However, rock which will likely require concentrated ripping with a single-tooth ripper or blasting was encountered above proposed grades in rock cores R-1 through R-5, R-7, R-8 and R-10 (refer to Figure 3 in Appendix I). In some areas, moderately hard to hard rock which will likely require blasting was encountered at depths  $1\frac{1}{2}$  to  $5\frac{1}{2}$  feet above the proposed finished grades (refer to Tables 4 and 5 in Appendix II). Additionally, subsurface conditions are often erratic and variations in the rock profile can occur in small lateral distances. Therefore, it is likely that very dense soils or rock pinnacles or ledges requiring difficult excavation techniques and/or blasting may be encountered in site areas intermediate of the performed borings.

If blasting is considered at the site, the designer may need to define vibration limits and incorporate vibration monitoring and/or crack surveys in the construction contract. Vibration from construction may cause some concern with surrounding property owners.

### **Culvert Foundation Investigation**

A double 8-foot wide by 6-foot high box culvert, approximately 200 feet long and covered by up to 25 feet of fill, will be constructed in the area of the drained pond and the existing creek. Alluvial soils were encountered to depths of 3 to 6 feet bgs in the area of the culvert. These fine grained, very soft soils should be removed prior to construction of the culvert. Additionally, these alluvial materials are unsuitable for use in embankment construction. These materials, once removed, may be used in thin layers to flatten slopes or may be wasted outside of the construction limits of the project.

We recommend that a 12-inch blanket of Type II foundation backfill material be placed under the barrel of the proposed culvert. Due to the groundwater elevations encountered in the culvert borings (approximate elevations 1042 to 1040 ft-MSL) and the existing creek, the proposed culvert area will likely not be able to be drained. Depending on the subgrade conditions encountered at the time of construction, it may be necessary to place a layer of filter fabric prior to backfill material placement below the culvert.

### **Wall Foundation Investigation**

A mechanically stabilized earth (MSE) retaining wall approximately 280 feet in length and up to 15 feet in height will be constructed near the southern end of the project just north of Warsaw Road Extension. Subsurface soils encountered in the proposed wall area consisted of approximately 8 feet of alluvial soils generally described as sandy clay, sandy silt or clayey silt with rock fragments and organic materials. These fine grained, very soft soils should be removed prior to construction of the retaining wall. The alluvial soils were underlain by residual soils generally described as silty sand. The groundwater elevations observed in borings W-1 and W-2 were 1 and 10 feet below the existing ground surface (approximate elevation of 1056 ft-MSL). Dewatering may be required to prevent the softening of foundation soils during construction.

The following minimum design parameters are recommended for use for the proposed MSE wall:

<b>Parameter</b>	<b>Value</b>
Cohesion, C	0 psf
Soil Unit Weight, $\gamma$	120 pcf
Angle of Internal Friction, $\phi$	30°
Coefficient of Sliding Friction, $\mu$	0.35

The maximum allowable soil bearing pressure recommended for the proposed wall is 3,000 psf. The bottom of the wall foundation should be embedded at least 3 feet below the existing groundline due to the presence of soft surficial soils in the area. If the MSE wall design pressure exceeds the maximum allowable pressure, then the wall should be constructed to a height

equivalent to the allowable bearing pressure, and after a 30-day waiting period, the wall may be constructed to its final height. Drainage through the wall should be included as part of the design and construction.

Due to the presence of very soft soils and shallow groundwater depths, it is recommended that the foundation soils be undercut three feet in depth and to two feet in depth outside the footing limits. The excavation should then be backfilled with structural backfill material and compacted to 98% maximum dry density.

### **Site Grading**

Prior to proceeding with construction, all vegetation, root systems, topsoil and other deleterious non-soil materials should be stripped from proposed construction areas. Clean topsoil may be stockpiled and subsequently re-used in landscaped areas. Debris-laden materials should be excavated, transported and disposed of off-site in accordance with appropriate solid waste rules and regulations. All existing utility locations should be reviewed to assess their impact on the proposed construction.

After clearing and stripping, areas which are at grade or will receive fill should be carefully evaluated by a geotechnical engineer. The engineer will require proof rolling of the subgrade with multiple passes of a 20 to 30 ton loaded truck or other pneumatic-tired vehicle of similar size and weight. The purpose of the proof rolling is to locate soft, weak, or excessively wet fill or residual soils present at the time of construction. Any unstable materials observed during the evaluation and proof rolling operations should be undercut and replaced with structural fill or stabilized in-place by scarifying and re-densifying.

Previously placed fill materials were encountered during this exploration. Based on our experience, we anticipate fill materials likely exist at other locations between our borings. Old fills are frequently erratic in composition and consistency. In the event that low consistency and/or debris laden fill materials are encountered during construction, typical recommendations would include undercutting and backfilling with structural fill and/or stabilizing in-place with fabric, stone, and/or other remedial techniques. Actual remedial recommendations can best be determined by the geotechnical engineer in the field at the time of construction.

Groundwater was encountered above or near planned grades in the areas of the proposed culvert and retaining wall and will have a significant impact on construction and the nature and extent of remedial subgrade improvement. We believe it would be prudent to schedule construction activities for the drier season of the year, typically late summer, early fall, when groundwater levels and rainfall are usually near their yearly minimum.

Excavations below groundwater may require the installation of a dewatering system. Even after the dewatering systems are installed, these residual materials will be water-softened and subject to degradation due to the high groundwater levels. Construction traffic should be minimized as much as practical to reduce the damage to the subgrade. However, regardless of the protective measures taken, we anticipate that undercutting and stabilization of portions of the residual soil subgrade will still be necessary.

Following undercutting of unstable residual soil areas, we anticipate stabilization of the subgrade will be needed using filter fabric and crushed stone to provide a stable base upon which to place and compact structural fill. If properly designed and installed, the geotextile/stone stabilization layer can be incorporated into the temporary and permanent dewatering systems. The actual extent of the necessary remedial actions required can best be determined in the field by the geotechnical engineer at the time of construction.

As previously mentioned, soft alluvial soils were encountered in the areas of the proposed culvert and retaining wall to depths ranging from 3 to 8 feet bgs. Prior to fill placement, a geotechnical engineer should carefully evaluate subgrade conditions in these areas. In the event that unstable soils are encountered, typical recommendations would include undercutting and replacing with structural fill/stone or stabilizing in-place with fabric and stone, as described below. A temporary dewatering system will be required in the event that groundwater exists at or near subgrade levels.

Stabilization of the exposed groundwater-softened subgrade will likely consist of a woven geotextile overlain by 1 to 2 feet of surge stone capped with 6 to 12 inches of #57 stone and/or compacted graded aggregate base (GAB). The actual extent and nature of the required remedial measures can best be determined in the field by the geotechnical engineer at the time of construction.

Very dense soils, auger refusal materials and/or rock were encountered in a majority of the borings performed at depths above planned grades. As a result, difficult excavation techniques and/or blasting will be required, or the planned grades will have to be raised. The gradation of material removed by ripping or blasting will probably be erratic. Re-use of these materials in fills will require additional effort and control. Preferably, the widespread use of these materials in structural fill areas should be avoided. Typically, approved fill areas where these materials may be used include landscaped areas or other non-structural fill areas, provided the upper limit (elevation) of these materials is at least 2 feet below design subgrade elevations. However, these materials may be placed in structural areas provided the upper limit (elevation) of these materials is at least 3 feet below design subgrade elevations of pavements and 5 feet below the bottom of spread foundations.

Rock pieces with thicknesses over 3 inches should not be incorporated into the fills. Soil should be intermixed with the rock materials in sufficient quantities to prevent void formation within the mass. The soils should be at or near their optimum moisture content. Lift thicknesses should remain as thin as practical and should not exceed 1 foot prior to compaction.

Heavy compaction equipment will be required in order to adequately compact the soil matrix to its required density and to break down the rock materials. Additional effort will be required to pulverize the dense materials in structural fill areas to provide well-compacted, relatively homogeneous fill. Our experience has been that these materials generally require at least 6 passes of heavy vibratory compaction equipment; however, we recommend that actual compaction requirements be determined in the field by the geotechnical engineer.



We recommend the use of an average swell factor of 30 percent for materials classified as hard rock.

## GENERAL COMMENTS

The analysis and recommendations presented in this report are based upon the data obtained from the borings performed at the indicated locations and from other information discussed in this report. This report does not reflect variations that may occur across the sites or due to the modifying effects of weather. The nature and extent of such variations may not become evident until during or after construction. If variations appear, Ranger Consulting, Inc. should be immediately notified so that further evaluation and supplemental recommendations can be provided.


This report has been prepared for the exclusive use of our client for specific application to the project discussed and has been prepared in accordance with generally accepted geotechnical engineering practices. No warranties, either expressed or implied, are intended or made. Site safety, excavation support, and dewatering requirements are the responsibility of others. In the event that any changes in the nature, design, or location of the project as outlined in this report are planned, the conclusions and recommendations contained in this report shall not be considered valid unless Ranger Consulting, Inc. reviews the changes, and either verifies or modifies the conclusions of this report in writing.

Report Prepared By: \_\_\_\_\_



Sandra A. Miller, PE  
GA PE No. 36138



Report Reviewed By: \_\_\_\_\_



Warren F. Bailey Jr., PE  
GA PE No. 11462

# *APPENDIX I*

## *Figures*



Site location outlined in red should be considered approximate.

Scale: Not to Scale  
 Drawn by: S. Miller  
 Date Drawn: 04/15/2015

**Project:**  
 Sun Valley Drive Extension  
 City of Roswell  
 Fulton County, Georgia

Site Location Map  
*Ranger Consulting, Inc.*


**Figure**  
**1**








Sun Valley Drive Extension  
 Figure 2  
 Boring Location Plan





 Silty Sand  
 Weathered Biotite Gneiss  
 Biotite Gneiss  
 REC - Recovery  
 RQD - Rock Quality Designation

**Scale:** Not to Scale  
**Drawn by:** S. Miller  
**Date Drawn:** 04/16/2015

**Project:**  
 Sun Valley Drive Extension  
 City of Roswell  
 Fulton County, Georgia

Rock Core Profile

*Ranger Consulting, Inc.*

Figure 3



Top of Core  
1040 ft-MSL



Rock Core R-1

Bottom  
of Core  
1034 ft-MSL

Top of Core  
1030 ft-MSL



Rock Core R-2

Bottom  
of Core  
1023 ft-MSL

Scale: Not to Scale  
Drawn by: S. Miller  
Date Drawn: 04/16/2015

**Project:**  
Sun Valley Drive Extension  
City of Roswell  
Fulton County, Georgia

Rock Core Photographs

*Ranger Consulting, Inc.*

**Figure**  
4



Top of Core  
1034 ft-MSL



Bottom  
of Core  
1030 ft-MSL

Rock Core R-3

Top of Core  
1035 ft-MSL



Bottom  
of Core  
1030 ft-MSL

Rock Core R-4

Scale: Not to Scale  
Drawn by: S. Miller  
Date Drawn: 04/16/2015

**Project:**  
Sun Valley Drive Extension  
City of Roswell  
Fulton County, Georgia

Rock Core Photographs

*Ranger Consulting, Inc.*

**Figure**  
4



Top of Core  
1040 ft-MSL



Bottom  
of Core  
1035 ft-MSL

Rock Core R-5

Top of Core  
1037 ft-MSL



Bottom  
of Core  
1031 ft-MSL

Rock Core R-6

Scale: Not to Scale  
Drawn by: S. Miller  
Date Drawn: 04/16/2015

**Project:**  
Sun Valley Drive Extension  
City of Roswell  
Fulton County, Georgia

Rock Core Photographs

*Ranger Consulting, Inc.*

**Figure**  
4



Top of Core  
1050 ft-MSL



Bottom  
of Core  
1045 ft-MSL

Rock Core R-7

Top of Core  
1042 ft-MSL



Bottom  
of Core  
1038 ft-MSL

Rock Core R-8

Scale: Not to Scale  
Drawn by: S. Miller  
Date Drawn: 04/16/2015

**Project:**  
Sun Valley Drive Extension  
City of Roswell  
Fulton County, Georgia

Rock Core Photographs

*Ranger Consulting, Inc.*

**Figure**  
4



Top of Core  
1039 ft-MSL



Bottom  
of Core  
1033 ft-MSL

Rock Core R-9

Top of Core  
1045 ft-MSL



Bottom  
of Core  
1036 ft-MSL

Rock Core R-10

Scale: Not to Scale  
Drawn by: S. Miller  
Date Drawn: 04/16/2015

**Project:**  
Sun Valley Drive Extension  
City of Roswell  
Fulton County, Georgia

Rock Core Photographs

*Ranger Consulting, Inc.*

**Figure**  
4

# ***APPENDIX II***

## ***Tables***

**TABLE 1  
SUMMARY OF LABORATORY TESTS**

Sun Valley Drive Extension  
Roswell, Fulton County, Georgia

Boring Number	B-1	B-2	B-3	B-4	B-5
Depth	0-20'	0-7'	0-8'	0-6'	0-13'
Description	Red brown micaceous silty clayey sand	Orange brown micaceous silty clayey sand	Orange brown micaceous silty clayey sand	Orange brown micaceous silty clayey sand	Brown micaceous silty clayey sand
1½" Sieve	100	100	100	100	100
¾" Sieve	99.8	99.6	99.4	98.0	99.7
#10 Sieve	83.4	84.3	81.4	74.9	86.4
#40 Sieve	70.2	65.9	63.8	56.5	70.7
#60 Sieve	63.6	57.5	56.6	48.7	63.4
200 Sieve	44.4	33.7	35.4	28.2	42.3
% Clay	25.5	10.6	14.5	11.9	21.3
Total Volume Change	15.5	17.4	10.3	8.0	11.0
% Swell	9.39	16.42	9.17	6.57	7.54
% Shrinkage	6.15	1.00	1.15	1.44	3.46
Max. Dry Density	116.2	118.9	119.0	119.3	117.5
% Optimum Moisture	14.5	13.0	12.5	12.5	14.0
% Natural Moisture	17.6	6.8	10.1	13.9	16.3
Liquid Limit	-	-	-	-	-
Plastic Limit	-	-	-	-	-
Plasticity Index	-	-	-	-	-
Erosion Index	4.72	5.95	5.83	6.69	4.96
Resistivity	-	-	-	-	-
pH	-	-	-	-	-
Classification	II-B3	I-A3	II-B2	I-A2	II-B2

**TABLE 1**  
**SUMMARY OF LABORATORY TESTS**

Sun Valley Drive Extension  
Roswell, Fulton County, Georgia

Sample Number	B-6	B-1D	B-5	B-6	SW-1
Depth	0-16'	18.5-20'	8.5-10'	8.5-10'	-
Description	Brown micaceous silty clayey sand	Grey orange tan micaceous silty sand (SM)	Brown micaceous silty sand (SM)	Red brown micaceous silty sand (SM)	Surface Water
1½" Sieve	100	100	100	100	-
¾" Sieve	99.5	100	100	100	-
#10 Sieve	83.1	82.0	85.4	95.7	-
#40 Sieve	62.4	60.0	62.7	83.5	-
#60 Sieve	53.9	49.5	53.4	72.8	-
200 Sieve	33.3	25.7	32.1	41.7	-
% Clay	13.8	7.6	16.8	11.2	-
Total Volume Change	15.8	-	-	-	-
% Swell	13.39	-	-	-	-
% Shrinkage	2.43	-	-	-	-
Max. Dry Density	116.4	-	-	-	-
% Optimum Moisture	13.6	-	-	-	-
% Natural Moisture	16.2	14.1	15.29	25.49	-
Liquid Limit	-	30	34	38	-
Plastic Limit	-	27	29	34	-
Plasticity Index	-	3	5	4	-
Erosion Index	6.07	4.84	6.19	4.96	-
Resistivity	-	-	-	-	18600
pH	-	-	-	-	6.54
Classification	II-B3	-	-	-	-

**TABLE 2**  
**SOIL BORING FILL, RESIDUAL AND AUGER REFUSAL DEPTHS**

Sun Valley Drive Extension  
Roswell, Fulton County, Georgia

Boring	Fill		Residual		Auger Refusal	
	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)
B-1	0-17	1058-1041	N/E	N/E	17	1041
B-1A	0-13	1059-1046	13-14	1046-1045	14	1045
B-1B	0-8	1060-1052	8-11	1052-1049	11	1049
B-1C	0-8	1060-1052	8-9	1052-1051	9	1051
B-1D	0-18	1057-1039	18-21	1039-1036	21	1036
B-1E	0-18	1059-1041	N/E	N/E	18	1041
B-1F	0-12	1060-1048	N/E	N/E	12	1048
B-2	N/E	N/E	0-2	1035-1033	2	1033
B-2A	N/E	N/E	0-7	1035-1028	7	1028
B-2B	N/E	N/E	0-2	1035-1033	2	1033
B-2C	N/E	N/E	0-2	1035-1033	2	1033
B-2D	N/E	N/E	0-2	1035-1033	2	1033
B-3	N/E	N/E	0-8	1033-1025	8	1025
B-4	N/E	N/E	0-6	1040-1034	6	1034
B-5	0-8	1053-1045	8-13	1045-1040	13	1040
B-6	0-6	1051-1045	6-16	1045-1035	16	1035
B-7	N/E	N/E	0-6	1052-1046	6	1046
B-8	N/E	N/E	0-3	1040-1037	3	1037
B-9	N/E	N/E	0-6	1038-1032	6	1032
B-10	0-12	1049-1037	N/E	N/E	12	1037
B-11	0-13	1047-1034	N/E	N/E	13	1034
B-12	0-18	1056-1038	N/E	N/E	18	1038
B-13	0-13	1058-1045	13-18	1045-1040	18	1040
B-14	0-8	1053-1045	8-15	1045-1038	15	1038
B-15	N/E	N/E	0-17	1053-1036	17	1036
HA-1	0-4	1046-1042	N/E	N/E	4	1042
HA-2	0-6	1047-1041	N/E	N/E	6	1041
HA-3	0-2	1045-1043	N/E	N/E	2	1043
HA-4	0-4	1057-1053	N/E	N/E	4	1053

**TABLE 3  
SOIL BORING ALLUVIUM, RESIDUAL AND AUGER REFUSAL DEPTHS**

Sun Valley Drive Extension  
Roswell, Fulton County, Georgia

Boring	Alluvium		Residual		Auger Refusal	
	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)
C-1	0-6	1043-1037	N/E	N/E	6	1037
C-2	0-3	1042-1039	3-5	1039-1037	5	1037
C-3	0-3	1044-1041	3-5	1041-1039	5	1039
W-1	0-8	1057-1049	8-16	1049-1041	16	1041
W-2	0-8	1066-1058	8-15	1058-1051	15	1051

**TABLE 4  
ROCK CORE DEPTHS**

Rock Core	Soil		Rippable Rock		Blast Rock		REC	RQD
	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)	Depth (ft)	Approx. Elev. (ft-MSL)		
R-1	0-19	1059-1040	21-23.5	1040-1037.5	23.5-25	1037.5-1034	71	36
R-2	0-5	1035-1030	5-5.5	1030-1029.5	5.5-12	1029.5-1023	90	70
R-3	0-6	1040-1034	6-6.5	1034-1033.5	6.5-10	1033.5-1030	98	50
R-4	0-5	1040-1035	N/E	N/E	5-10	1035-1030	89	31
R-5	0-13	1053-1040	N/E	N/E	13-18	1040-1035	82	28
R-6	0-14	1051-1037	14-14.5	1037-1036.5	14.5-20	1036.5-1031	100	71
R-7	0-10	1060-1050	10-12	1050-1048	12-15	1048-1045	98	18
R-8	0-16	1058-1042	16-17	1042-1041	17-20	1041-1038	82	19
R-9	0-14	1053-1039	14-16.5	1039-1036.5	16.5-20	1036.5-1033	88	32
R-10	0-6	1051-1045	N/E	N/E	6-15	1045-1036	93	49

**TABLE 5**  
**ROCK CORE AND PROPOSED GROUND SURFACE ELEVATIONS**

Sun Valley Drive Extension  
 Roswell, Fulton County, Georgia

<b>Rock Core</b>	<b>Proposed Elevation (ft-MSL)</b>	<b>Rippable Rock Approx. Elev. (ft-MSL)</b>	<b>Blast Rock Approx. Elev. (ft-MSL)</b>	<b>REC</b>	<b>RQD</b>
R-1	1036	1040	1037.5	71	36
R-2	1025	1030	1029.5	90	70
R-3	1028	1034	1033.5	98	50
R-4	1032	N/E	1035	89	31
R-5	1038	N/E	1040	82	28
R-6	1037	1037	1036.5	100	71
R-7	1044	1050	1048	98	18
R-8	1038	1042	1041	82	19
R-9	1041	1039	1036.5	88	32
R-10	1041	N/E	1045	93	49



pH   
 Resistivity

Project: Sun Valley Drive Extension

City: Roswell

County: Fulton

Table 6

## Pipe Culvert Material Alternates For Piedmont/Blue Ridge Region

TYPE OF PIPE INSTALLATION	CONCRETE	CORRUGATED STEEL AASHTO M-36		CORRU-GATED ALUMINUM AASHTO M-196	PLASTIC					
		ALUMINUM COATED (TYPE 2) CORR. STEEL	PLAIN ZINC COATED	PLAIN UNCOATED ALUMINUM	CORR. POLY- ETHYLENE AASHTO M-252	CORR. POLY- ETHYLENE SMOOTHED LINED AASHTO M-294 TYPE "S"	POLY VINYL CHLORIDE (PVC) PROFILE WALL AASHTO M-304	POLY VINYL CHLORIDE (PVC) CORRUGATED SMOOTH INTERIOR ASTM F-949		
LONGITUDINAL INTERSTATE AND TRAVEL BEARING	<b>X</b>									
LONGITUDINAL NON- INTERSTATE AND NON- TRAVEL BEARING	<b>X</b>	<b>X</b>		<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>		
STORM DRAINS DRAIN	CROSS GRADE ≤ 10%	ADT < 250	<b>X</b>	<b>X</b>	<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>	
		250 < ADT < 1,500	<b>X</b>	<b>X*</b>		<b>X</b>		<b>X</b>	<b>X</b>	
		1,500 < ADT < 15,000	<b>X</b>					<b>X</b>	<b>X</b>	<b>X</b>
		ADT > 15,000	<b>X</b>							
	GRADE > 10%	ADT < 250		<b>X</b>	<b>X</b>	<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>
		ADT > 250				<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>
SIDE DRAIN	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>		
PERMANENT SLOPE DRAIN		<b>X</b>	<b>X</b>	<b>X</b>		<b>X</b>	<b>X</b>	<b>X</b>		
PERFORATED UNDERDRAIN		<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>		<b>X</b>		

\* This type pipe can be used if the addition of Type "B" Coating (AASHTO M-190, Half Bituminous Coated with Paved Invert) is utilized.

**NOTES:**

- 1 Allowable materials are indicated by an "X".
- 2 Structural requirements of storm drain pipe will be in accordance with Georgia Standard 1030-D or 1030-P, whichever is applicable, and the Standard Specifications.
- 3 Graded aggregate backfill shall be used in cross drain applications for all plastic pipes (AASHTO M-294, HDPE pipe; AASHTO M-304, PVC pipe; ASTM F-949, PVC pipe).
- 4 The Contractor shall provide additional storm sewer capacity calculations if a pipe material other than concrete is selected.
- 5 Pipe used under mechanically stabilized earth (MSE) walls, within MSE wall backfill, or within five feet of an MSE wall face shall be Class V Concrete Pipe.
- 6 Project specific pH and Resistivity values are entered into the respective boxes above to determine allowable pipe materials.

# ***APPENDIX III***

## ***Boring Logs***

# Ranger Consulting, Inc.

**BORING NO.: B-1**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1058 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches FILL: Stiff red brown micaceous fine sandy silt	ML							
5	1055					1		12		
10	1050	Medium dense grey brown silty medium to fine sand with organic fragments and topsoil	SM			2		11		
15	1045					3		14		
20	1040	Auger Refusal at 17 feet								
25	1035									
30	1030									
	1025									






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-1A**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1059 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> FILL: Stiff red brown micaceous fine sandy silt	ML							
5	1055					1		12		
10	1050	Stiff brown micaceous fine sandy silt with organic fragments and topsoil				2		11		
15	1045	RESIDUAL: Very dense orange brown micaceous silty coarse to fine sand Auger Refusal at 14 feet	SM			3		100/6"		
20	1040									
25	1035									
30	1030									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-1B**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1060 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1060	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> FILL: Loose red brown micaceous silty medium to fine sand	SM							
5	1055				1		9			
10	1050	RESIDUAL: Very dense tan orange micaceous silty coarse to fine sand with rock fragments	SM		2		56			
		Auger Refusal at 11 feet								
15	1045									
20	1040									
25	1035									
30	1030									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-1C**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1060 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1060	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px; width: fit-content;">           TOPSOIL: 2 inches         </div> FILL: Red brown micaceous coarse to fine sandy silt	ML							
5	1055									
		RESIDUAL: Brown micaceous silty medium to fine sand	SM							
10	1050	Auger Refusal at 9 feet								
15	1045									
20	1040									
25	1035									
30	1030									








Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-1D**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1057 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches								
		FILL: Very stiff red brown micaceous fine sandy silt	ML							
5						1		17		
		Firm red brown micaceous fine sandy silt								
10						2		8		
		No Sample Recovered (13.5 - 15 feet)								
15						3		6		
		RESIDUAL: Very dense grey orange tan micaceous silty medium to fine sand	SM							
20						4		100/10"		
		Auger Refusal at 21 feet								
25										
30										

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-1E**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1059 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> FILL: Stiff red brown micaceous silty fine sand	SM							
5	1055					1		10		
10	1050	Medium dense orange grey micaceous silty medium to fine sand				2		17		
15	1045	Firm brown micaceous fine sandy clay with rock fragments	CL			3		7		
20	1040	Auger Refusal at 18 feet								
25	1035									
30	1030									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.









# Ranger Consulting, Inc.

**BORING NO.: B-1F**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1060 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1060	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> FILL: Loose brown micaceous silty fine sand	SM							
5	1055					1		10		
10	1050	Very dense brown micaceous silty coarse to fine sand				2		100/10"		
12		Auger Refusal at 12 feet								
15	1045									
20	1040									
25	1035									
30	1030									



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-2**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	TOPSOIL: 2 inches RESIDUAL: Very dense orange brown micaceous silty coarse to fine sand with rock fragments Auger Refusal at 2 feet	SM			1		100/8"		
5	1030									
10	1025									
15	1020									
20	1015									
25	1010									
30	1005									





Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-2A**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> RESIDUAL: Very dense red brown micaceous silty medium to fine sand	SM			1		100/4"		
						2		100/12"		
5	1030	Auger Refusal at 7 feet								
10	1025									
15	1020									
20	1015									
25	1010									
30	1005									


Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-2B**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	<div style="border: 1px solid black; padding: 2px; margin-bottom: 2px;">TOPSOIL: 2 inches</div> <div style="border: 1px solid black; padding: 2px;">RESIDUAL: Very dense brown micaceous silty medium to fine sand with rock fragments</div>	SM			1	■	100/8"		
		Auger Refusal at 2 feet								
5	1030									
10	1025									
15	1020									
20	1015									
25	1010									
30	1005									



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-2C**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> RESIDUAL: Very dense red brown micaceous silty medium to fine sand	SM			1		100/12"		
		Auger Refusal at 2 feet								
5	1030									
10	1025									
15	1020									
20	1015									
25	1010									
30	1005									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-2D**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> RESIDUAL: Very dense grey orange brown micaceous silty medium to fine sand Auger Refusal at 2 feet	SM			1		100/12"		
5	1030									
10	1025									
15	1020									
20	1015									
25	1010									
30	1005									






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-3**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1033 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches								
		RESIDUAL: Medium dense orange brown micaceous silty medium to fine sand	SM			1		26		
1030		Very dense orange brown micaceous silty medium to fine sand with rock fragments				2		100/12"		
5						3		100/10"		
1025		Auger Refusal at 8 feet								
10										
1020										
15										
1015										
20										
1010										
25										
1005										
30										
1000										






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-4**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1040 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1040	TOPSOIL: 3 inches RESIDUAL: Medium dense orange brown micaceous silty fine sand	SM			1		15		
5	1035	Dense brown micaceous fine sandy clay	CL			2		32		
		Auger Refusal at 6 feet								
10	1030									
15	1025									
20	1020									
25	1015									
30	1010									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.













# Ranger Consulting, Inc.

**BORING NO.: B-5**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1053 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 4 inches								
		FILL: Stiff red brown micaceous clayey fine sand	SC			1		11		
	1050	Medium dense brown micaceous silty medium to fine sand	SM			2		12		
5		Stiff brown micaceous fine sandy silt with topsoil	ML			3		14		
	1045	RESIDUAL: Medium dense brown micaceous silty medium to fine sand	SM			4		24		
10										
	1040	Auger Refusal at 13 feet								
15										
	1035									
20										
	1030									
25										
	1025									
30										
	1020									













Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-6**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-24-2015  
 ELEVATION: 1051 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : 8 ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0										
	1050	TOPSOIL: 4 inches	SM							
		FILL: Medium dense to loose brown micaceous silty medium to fine sand	SM			1		12		
		Loose brown micaceous clayey medium to fine sand	SC			2		10		
5										
	1045	RESIDUAL: Very dense white brown micaceous silty medium to fine sand	SM			3		51		
		Medium dense red brown micaceous silty medium to fine sand			$\sphericalangle$	4		14		
10										
	1040									
		Very dense tan brown micaceous silty coarse to fine sand				5		100/6"		
15										
	1035	Auger Refusal at 16 feet								
20										
	1030									
25										
	1025									
30										
	1020									





Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-7**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1052 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches								
	1050	RESIDUAL: Medium dense orange brown micaceous silty medium to fine sand with rock fragments	SM			1		25		
5		Auger Refusal at 6 feet								
	1045									
10										
	1040									
15										
	1035									
20										
	1030									
25										
	1025									
30										
	1020									



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-8**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1040 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1040	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 3 inches</div> RESIDUAL: Brown micaceous silty medium to fine sand	SM							
5	1035	Auger Refusal at 3 feet								
10	1030									
15	1025									
20	1020									
25	1015									
30	1010									




Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-9**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1038 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 3 inches</div> RESIDUAL: Dense orange brown micaceous silty medium to fine sand	SM							
5	1035	Auger Refusal at 6 feet				1		33		
10	1030									
15	1025									
20	1020									
25	1015									
30	1010									
	1005									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-10**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1049 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 4 inches</div> FILL: Stiff red brown micaceous clayey silt	ML							
5	1045					1		14		
10	1040	Stiff red brown micaceous clayey silt with rock fragments				2		10		
15	1035	Auger Refusal at 12 feet								
20	1030									
25	1025									
30	1020									







Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-11**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER > Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1047 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING >  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 3 inches								
		FILL: Very stiff red brown sandy silt with clay	CL-ML							
5						1		27		
10		Medium dense red brown silty medium to fine sand with clay and rock fragments	SM			2		15		
13		Auger Refusal at 13 feet								
15										
20										
25										
30										






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-12**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1056 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1055	TOPSOIL: 4 inches FILL: Very stiff brown micaceous fine sandy silt	ML							
5	1050	Medium dense red brown micaceous silty medium to fine sand	SM							
10	1045				2		13			
15	1040				3		16			
20	1035	Auger Refusal at 18 feet								
25	1030									
30	1025									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.



# Ranger Consulting, Inc.

**BORING NO.: B-13**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1058 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 4 inches		▽▽▽▽						
		FILL: Stiff brown micaceous fine sandy silt with rock fragments	ML							
5	1055					1	▴	13		
10	1050					2	▴	7		
15	1045	RESIDUAL: Medium dense brown tan micaceous silty medium to fine sand	SM			3	▴	25		
20	1040	Auger Refusal at 18 feet		↑						
25	1035									
30	1030									
	1025									








Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-14**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1053 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 4 inches</div> FILL: Dense orange brown micaceous silty coarse to fine sand with clay and rock fragments	SM							
5	1050					1		46		
10	1045	RESIDUAL: Medium dense brown micaceous silty fine sand	SM			2		24		
15	1040	Very dense brown micaceous silty fine sand				3		100/6"		
		Auger Refusal at 15 feet								
20	1035									
25	1030									
30	1025									
	1020									







Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: B-15**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-30-2015  
 ELEVATION: 1053 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 4 inches								
		RESIDUAL: Very dense orange brown micaceous silty medium to fine sand	SM							
5	1050					1		51		
10	1045	Very dense orange brown micaceous silty medium to fine sand with rock fragments				2		100/8"		
15	1040					3		18		
20	1035	Auger Refusal at 17 feet								
25	1030									
30	1025									
	1020									



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: HA-1**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Hand Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1046 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1045	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px; width: fit-content;">TOPSOIL: 2 inches</div> FILL: Red brown micaceous fine sandy silt	ML							
5	1040	Hand Auger Refusal at 4 feet								
10	1035									
15	1030									
20	1025									
25	1020									
30	1015									



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: HA-2**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Hand Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1047 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 1 inch	ML							
		FILL: Red brown micaceous medium to fine sandy silt with rock fragments								
1045										
5										
1040		Hand Auger Refusal at 6 feet								
10										
1035										
15										
1030										
20										
1025										
25										
1020										
30										
1015										



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: HA-3**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Hand Auger  
 DEPTH TO WATER> Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1045 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1045	<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> FILL: Red brown micaceous medium to fine sandy silt with rock fragments	ML							
		Hand Auger Refusal at 2 feet								
5	1040									
10	1035									
15	1030									
20	1025									
25	1020									
30	1015									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: HA-4**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Hand Auger  
 DEPTH TO WATER > Initial  $\nabla$ : N/E After 24 Hours  $\nabla$ : N/E

DATE: 03-25-2015  
 ELEVATION: 1057 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING >  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 3 inches		▧						
		FILL: Red brown micaceous medium to fine sandy silt	ML	▧						
5		Hand Auger Refusal at 4 feet		↑						
1055										
1050										
10										
1045										
15										
1040										
20										
1035										
25										
1030										
30										
1025										







Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: C-1**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : 3      After 24 Hours  $\nabla$ : 2

DATE: 03-25-2015  
 ELEVATION: 1043 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ :      ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches	SM							
		ALLUVIUM: Very loose brown tan micaceous silty coarse to fine sand			$\nabla$	1		0		
1040		Very soft brown micaceous medium to fine sandy silt	ML		$\nabla$	2		2		
5		Auger Refusal at 6 feet								
1035										
10										
1030										
15										
1025										
20										
1020										
25										
1015										
30										
1010										

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.









# Ranger Consulting, Inc.

**BORING NO.: C-2**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : 2 After 24 Hours  $\nabla$ : 2

DATE: 03-25-2015  
 ELEVATION: 1042 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches								
	1040	ALLUVIUM: Very soft red brown micaceous silty clay with organic fragments	CL-ML		$\nabla$	1		0		
5		RESIDUAL: Very hard grey green micaceous silty coarse to fine sand with clay and rock fragments	SM			2		100/6"		
	1035	Auger Refusal at 5 feet								
10										
	1030									
15										
	1025									
20										
	1020									
25										
	1015									
30										
	1010									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: C-3**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : 2 After 24 Hours  $\nabla$ : 2

DATE: 03-25-2015  
 ELEVATION: 1044 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">TOPSOIL: 2 inches</div> ALLUVIUM: Very soft brown fine sandy clay with organic fragments	CL			1		0		
5	1040	RESIDUAL: Very hard grey brown micaceous silty fine sand	SM			2		100/10"		
		Auger Refusal at 5 feet								
10	1035									
15	1030									
20	1025									
25	1020									
30	1015									












Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: W-1**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : 13 After 24 Hours  $\nabla$ : 1

DATE: 04-01-2015  
 ELEVATION: 1057 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		TOPSOIL: 2 inches	CL		$\nabla$					
		ALLUVIUM: Very soft orange brown fine sandy clay with organic fragments	CL			1		2		
	1055									
		Firm tan orange micaceous fine sandy silt	ML			2		7		
5										
	1050					3		6		
		RESIDUAL: Medium dense orange brown micaceous silty fine sand	SM			4		13		
10										
	1045				$\nabla$	5		30		
15						6		27		
	1040	Auger Refusal at 16 feet								
20										
	1035									
25										
	1030									
30										
	1025									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: W-2**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: 3-1/4" Hollow Stem Auger  
 DEPTH TO WATER> Initial  $\nabla$ : 12 After 24 Hours  $\nabla$ : 10

DATE: 04-01-2015  
 ELEVATION: 1066 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1066	TOPSOIL: 2 inches ALLUVIUM: Firm to stiff red brown clayey silt with rock fragments	ML			1		6		
5	1060					2		11		
						3		10		
10	1055	RESIDUAL: Medium dense white brown micaceous silty medium to fine sand	SM		$\nabla$	4		12		
					$\nabla$	5		22		
15	1050	Very dense white brown micaceous silty coarse to fine sand with rock fragments Auger Refusal at 15 feet				6		100/8"		
20	1045									
25	1040									
30	1035									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# KEY TO SYMBOLS

Symbol Description

## Strata symbols



Topsoil



Silt



Silty sand



Low plasticity  
clay



Clayey sand



Silty low plasticity  
clay

## Misc. Symbols



Drill refusal



Depth to caving



Water depth at least 24 hours  
after drilling

## Soil Samplers



Standard penetration test

## Notes:






1. Exploratory soil borings were drilled on 03-24-2015, 03-25-2015 and 03-30-2105 to 04-01-2015 using a 3-1/4 inch diameter hollow stem continuous flight power auger.
2. The rock core borings were drilled on 03-31-2015 and 04-01-2015 using a mud rotary techniques with a tri-cone bit through the soil and a 1-7/8 inch diameter NQWL bit to core the rock.
3. Boring locations were taped from existing features and elevation extrapolated from the provided topographic plan.
4. These logs are subject to the limitations, conclusions, and recommendations in this report.

# Ranger Consulting, Inc.

**BORING NO.: R-1**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1059 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		Brown silty sand	SM							
5	1055									
10	1050									
15	1045									
20	1040	Moderately soft to soft brown fragmented to weathered incompetent biotite gneiss							71	36
		Moderately hard to hard white grey solid incompetent biotite gneiss with quartz								
25	1035	Coring Terminated at 25 feet								
30	1030									





Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-2**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1035 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1035	Grey brown silty sand	SM							
5	1030	Soft brown weathered competent biotite gneiss Moderately hard grey white broken biotite gneiss							90	70
10	1025	Coring Terminated at 12 feet								
15	1020									
20	1015									
25	1010									
30	1005									




Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-3**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER > Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 04-01-2015  
 ELEVATION: 1040 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING >  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1040	Grey green silty sand	SM							
5	1035	Soft dark brown grey weathered competent biotite gneiss Medium soft to medium hard brown white grey fractured biotite gneiss							98	50
10	1030	Coring Terminated at 10 feet								
15	1025									
20	1020									
25	1015									
30	1010									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.







# Ranger Consulting, Inc.

**BORING NO.: R-4**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 04-01-2015  
 ELEVATION: 1040 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1040	Grey green silty sand	SM							
5	1035	Moderately soft to moderately hard grey brown white fragmented to fractured biotite gneiss							89	31
10	1030	Coring Terminated at 10 feet								
15	1025									
20	1020									
25	1015									
30	1010									




Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-5**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1053 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		Brown silty sand	SM							
1050										
5										
1045										
10										
1040		Soft brown weathered incompetent biotite gneiss							82	28
15		Moderately soft to moderately hard brown grey fragmented to fractured biotite gneiss								
		Moderately hard grey white broken biotite gneiss with quartz								
1035		Coring Terminated at 18 feet								
20										
1030										
25										
1025										
30										
1020										





Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-6**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 04-01-2015  
 ELEVATION: 1051 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1050	Grey brown silty sand	SM							
5	1045									
10	1040									
15	1035									
		Soft brown weathered competent biotite gneiss							100	71
		Soft to moderately soft weathered to fragmented competent biotite gneiss								
		Moderately hard grey white broken to solid competent biotite gneiss								
20	1030	Coring Terminated at 20 feet								
25	1025									
30	1020									






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-7**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1060 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1060	Grey brown silty sand	SM							
5	1055									
10	1050	Soft to moderately soft grey brown weathered incompetent biotite gneiss							98	18
		Moderately soft to soft grey brown white fragmented to weathered biotite gneiss with quartz								
15	1045	Coring Terminated at 15 feet								
20	1040									
25	1035									
30	1030									






Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-8**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER > Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1058 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING >  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		Grey brown silty sand	SM							
5										
10										
15		Soft brown weathered incompetent biotite gneiss							82	19
20		Moderately soft to moderately hard brown grey white fractured incompetent biotite gneiss with quartz								
25		Coring Terminated at 20 feet								
30										





Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-9**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 04-01-2015  
 ELEVATION: 1053 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\sphericalangle$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0		Grey brown silty sand	SM							
1050										
5										
1045										
10		Soft brown weathered incompetent biotite gneiss					88	32		
15										
1040		<u>Moderately soft brown grey fractured incompetent biotite gneiss</u> Moderately hard to hard white grey broken incompetent biotite gneiss								
1035										
20		Coring Terminated at 20 feet								
1030										
25										
1025										
30										
1020										



Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# Ranger Consulting, Inc.

**BORING NO.: R-10**

PROJECT: Sun Valley Drive Extension  
 CLIENT: McGee Partners, Inc.  
 LOCATION: Roswell, Fulton County, Georgia  
 DRILL / METHOD: Mud Rotary, NQWL Rock Coring  
 DEPTH TO WATER> Initial  $\nabla$ : N/O After 24 Hours  $\nabla$ : N/O

DATE: 03-31-2015  
 ELEVATION: 1051 ft-MSL  
 LOGGED BY: K. Young  
 CREW CHIEF: B. Ozment  
 DEPTH TO CAVING>  $\nabla$ : ft

Depth (feet)	Elevation (ft-MSL)	Strata Description	USCS	Graphic	Groundwater	Sample Number	Sample Type	N-Value	% Rock Recovery	% Rock RQD
0	1050	Grey brown silty sand	SM							
5	1045	Soft brown weathered competent biotite gneiss							93	49
		Moderately soft to moderately hard brown grey white fractured competent biotite gneiss with quartz								
10	1040									
15	1035	Coring Terminated at 20 feet								
20	1030									
25	1025									
30	1020									

Notes: N/E - Not Evident; N/O - Not Observed  
 Boring elevations were interpolated from the provided topographic plan and should therefore be considered approximate.  
 This information pertains only to this boring and should not be considered indicative of the site.

# KEY TO SYMBOLS

Symbol Description

## Strata symbols



Silty sand



Weathered metamorphic rocks



Metamorphic  
rocks

## Misc. Symbols



Drill refusal

## Soil Samplers



Rock core

## Notes:

1. Exploratory soil borings were drilled on 03-24-2015, 03-25-2015 and 03-30-2105 to 04-01-2015 using a 3-1/4 inch diameter hollow stem continuous flight power auger.
2. The rock core borings were drilled on 03-31-2015 and 04-01-2015 using a mud rotary techniques with a tri-cone bit through the soil and a 1-7/8 inch diameter NQWL bit to core the rock.
3. Boring locations were taped from existing features and elevation extrapolated from the provided topographic plan.
4. These logs are subject to the limitations, conclusions, and recommendations in this report.



# ***APPENDIX IV***

## ***Laboratory Results***



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**  
Date **04/01/15**  
Checked By **18**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19738/B-1	Depth/Elev.	0-20'
Location	-	Add. Info	-

**GDT-7**


**Method of Test for Determining Maximum Density of Soils**

SAMPLE DATA	MOISTURE CONTENT			
	Air-Dried	Oven-Dried*	Natural	Air-Dry Material
Total Mass of Soil before sieving, g	19650.0	18238.3	332.20	533.20
Mass of Mat. retained on No.10 sieve, g		3020.9	296.70	500.90
Material Retained on No.10 sieve, %		16.6	94.80	83.60
Note: Values based on calculated oven-dried mass			17.6	7.7

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6		
Mass of Mold and Soil, g	6103.0	6164.0	6184.0	6153.0			Mold ID Number	314
Mass of Wet Sample & Tare, g	518.6	580.1	536.6	569.1			Mass of Mold, g	4211.3
Mass of Dry Sample & Tare, g	466.6	516.8	475.6	495.6			Volume of Mold, ft <sup>3</sup>	0.0333
Mass of Tare, g	125.8	124.4	130.3	125.6			Hammer ID Number	318
Moisture Content, %	15.3	16.1	17.7	19.9			Number of Blows per layer	25
							Number of Layers	3
Wet Density, pcf	125.2	129.3	130.6	128.5				
Dry Density, pcf	108.7	111.3	111.0	107.2				



Maximum Dry Density, pcf	<b>111.8</b>	Optimum Moisture Content, %	<b>16.8</b>
Absorption, % (assumed)	<b>2</b>	Corrected Maximum Dry Density, pcf	<b>116.2</b>
		Corrected Optimum Moisture Content, %	<b>14.5</b>

USCS (ASTM D2487; D2488)	<b>NA</b>	DESCRIPTION	<b>NA</b>
AASHTO (M 145)	<b>NA</b>		
GA DOT	<b>NA</b>		



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	RI
Date	04/01/15
Checked By	<i>RB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19738/B-1	Depth/Elev.	0-20'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	111.8
Optimum Moisture Content (O.M.C.), %	16.8

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	16.8

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1113.79

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	533.20	538.60
Mass of Dry Soil and Tare, g	500.90	473.20
Mass of Tare, g	83.60	89.20
Moisture Content, %	7.7	17.0
<b>Water Adjustment, g</b>	<b>100.9</b>	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.126	Swell, %	<b>9.39</b>
Final Dial Gage Reading, inch	0.220	Swell Mold ID #	231
Change in Dial Gage Readings, inch	0.094	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height			
Initial Dial Gage Reading, inch	0.758	Diameter	Original Volume, in <sup>3</sup>	12.67
Final Dial Gage Reading, inch	0.731	0.678	Final Volume, in <sup>3</sup>	11.89
Preset Dial Gage Gap, inch	0.250	3.250	Shrinkage, %	<b>6.15</b>
Dial Gage ID #	360	359	Shrink Mold ID #	201
Stand ID #	55	177		

Proctor Dry Density (Minus No. 10 Material), pcf	111.8
% Retained on No. 10 Sieve	16.6
Conversion Factor	0.855

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>15.5</b>	<b>13.3</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084  
Phone: 770-938-8233  
Fax: 770-923-8973  
Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**  
Date **04/01/15**  
Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19738/B-1	Depth/Elev.	0-20'
Location	-	Add. Info	-

**GDT-4**


**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	332.2	Mass of Wet Sample & Tare, g	533.20
Mass of Dry Sample & Tare, g	296.7	Mass of Dry Sample & Tare, g	500.90
Mass of Tare, g	94.8	Mass of Tare, g	83.60
Moisture Content, %	17.6	Moisture Content, %	7.7
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	19650.0	Mass of Air-Dried Fine Material & Tare, g	53.90
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	18238.3	Mass of Dry Fine Material, g	50.03
		% of Total Sample Passing No. 10 Sieve	83.4

**SIEVE ANALYSIS**

<b>GRADATION OF PLUS NO.10 Material</b>				<b>GRADATION OF MINUS NO.10 Material</b>						
Mass of Tare, g	0.0			Mass of Tare, g	0.0					
	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing	
Sieve Size										
1.5"	0.0	0.0	0.0	100.0	#40	7.94	7.94	15.9	84.1	70.2
.75"	34.3	34.3	0.2	99.8	#60	11.90	11.90	23.8	76.2	63.6
#10	3020.9	3020.9	16.6	83.4	#200	23.39	23.39	46.8	53.2	44.4
					Total	34.76	34.76	69.5	-	
					Clay (Effluent)				30.5	25.5

**Particle Size Distribution**



GA DOT	Class	Sub-class
	NA	NA

Soil Classification (AASHTO M-145)	
% Gravel	16.6
% COARSE Sand	13.2
% FINE Sand	25.8
% FINES (Silt-Clay)	44.4
% Clay	25.5
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
NA	NA	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**  
Date **04/01/15**  
Checked By **18**

Client Pr. # **150411-007**  
Pr. Name **Sun Valley Drive Extension**  
Sample ID **19739/B-2**  
Location **-**

Lab. PR. # **1595-02-1**  
S. Type **Bulk**  
Depth/Elev. **0-7'**  
Add. Info **-**

**GDT-7**

**Method of Test for Determining Maximum Density of Soils**

**SAMPLE DATA**

	Air-Dried	Oven-Dried*
Total Mass of Soil before sieving, g	16567.2	15744.1
Mass of Mat. retained on No.10 sieve, g		2467.7
Material Retained on No.10 sieve, %		15.7

Note: Values based on calculated oven-dried mass

**MOISTURE CONTENT**


	Natural	Air-Dry Material
Mass of Wet Sample & Tare, g	313.80	470.70
Mass of Dry Sample & Tare, g	300.30	453.50
Mass of Tare, g	102.70	124.50
Moisture Content, %	6.8	5.2

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6
Mass of Mold and Soil, g	6117.0	6184.0	6210.0	6193.0		
Mass of Wet Sample & Tare, g	600.5	610.0	616.0	623.6		
Mass of Dry Sample & Tare, g	556.2	556.8	559.8	562.3		
Mass of Tare, g	183.4	176.1	182.2	182.4		
Moisture Content, %	11.9	14.0	14.9	16.1		
Wet Density, pcf	126.2	130.6	132.3	131.2		
Dry Density, pcf	112.8	114.6	115.2	113.0		

Mold ID Number	314
Mass of Mold, g	4211.3
Volume of Mold, ft <sup>3</sup>	0.0333
Hammer ID Number	318
Number of Blows per layer	25
Number of Layers	3



<b>Maximum Dry Density, pcf</b>	<b>115.2</b>	<b>Optimum Moisture Content, %</b>	<b>14.9</b>
Absorption, % (assumed) <b>2</b>			
<b>Corrected Maximum Dry Density, pcf</b>	<b>118.9</b>	<b>Corrected Optimum Moisture Content, %</b>	<b>13.0</b>

USCS (ASTM D2487; D2488)

**NA**

DESCRIPTION

**NA**

AASHTO (M 145)

**NA**

Class Sub-class

GA DOT

**NA** **NA**



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/01/15**

Checked By **RB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19739/B-2	Depth/Elev.	0-7'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	115.2
Optimum Moisture Content (O.M.C.), %	14.9

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	14.9

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1140.38

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	470.70	530.00
Mass of Dry Soil and Tare, g	453.50	473.70
Mass of Tare, g	124.50	94.00
Moisture Content, %	5.2	14.8
<b>Water Adjustment, g</b>	<b>110.3</b>	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.130	Swell, %	<b>16.42</b>
Final Dial Gage Reading, inch	0.295	Swell Mold ID #	228
Change in Dial Gage Readings, inch	0.165	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height			
Initial Dial Gage Reading, inch	0.748	Diameter	Original Volume, in <sup>3</sup>	12.54
Final Dial Gage Reading, inch	0.745	0.736	Final Volume, in <sup>3</sup>	12.42
Preset Dial Gage Gap, inch	0.250	3.250	Shrinkage, %	<b>1.00</b>
Dial Gage ID #	360	359	Shrink Mold ID #	201
Stand ID #	55	177		

Proctor Dry Density (Minus No. 10 Material), pcf	115.2
% Retained on No. 10 Sieve	15.7
Conversion Factor	0.860

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>17.4</b>	<b>15.0</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/02/15**

Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19739/B-2	Depth/Elev.	0-7'
Location	-	Add. Info	-

**GDT-4**


**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	313.8	Mass of Wet Sample & Tare, g	470.70
Mass of Dry Sample & Tare, g	300.3	Mass of Dry Sample & Tare, g	453.50
Mass of Tare, g	102.7	Mass of Tare, g	124.50
Moisture Content, %	6.8	Moisture Content, %	5.2
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	16567.2	Mass of Air-Dried Fine Material & Tare, g	52.62
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	15744.1	Mass of Dry Fine Material, g	50.01
		% of Total Sample Passing No. 10 Sieve	84.3

**SIEVE ANALYSIS**

<b>GRADATION OF PLUS NO.10 Material</b>				<b>GRADATION OF MINUS NO.10 Material</b>						
Mass of Tare, g	0.0			Mass of Tare, g	0.0					
Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing
1.5"	0.0	0.0	0.0	100.0	#40	10.93	10.93	21.9	78.1	65.9
.75"	64.1	64.1	0.4	99.6	#60	15.89	15.89	31.8	68.2	57.5
#10	2467.7	2467.7	15.7	84.3	#200	30.00	30.00	60.0	40.0	33.7
					Total	43.70	43.70	87.4	-	
					Clay (Effluent)				12.6	10.6

**Particle Size Distribution**



Class	Sub-class
GA DOT <b>NA</b>	<b>NA</b>

<b>Soil Classification (AASHTO M-145)</b>	
% Gravel	15.7
% COARSE Sand	18.4
% FINE Sand	32.2
% FINES (Silt-Clay)	33.7
% Clay	10.6
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
<b>NA</b>	<b>NA</b>	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

RI

Date

04/01/15

Checked By

18

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19740/B-3
Location	-

Lab. PR. #	1595-02-1
S. Type	Bulk
Depth/Elev.	0-8'
Add. Info	-

**GDT-7**

**Method of Test for Determining Maximum Density of Soils**

**SAMPLE DATA**

	Air-Dried	Oven-Dried*
Total Mass of Soil before sieving, g	17826.1	17068.1
Mass of Mat. retained on No.10 sieve, g		3171.8
Material Retained on No.10 sieve, %		18.6

Note: Values based on calculated oven-dried mass

**MOISTURE CONTENT**


	Natural	Air-Dry Material
Mass of Wet Sample & Tare, g	345.40	533.10
Mass of Dry Sample & Tare, g	323.00	515.90
Mass of Tare, g	101.30	128.60
Moisture Content, %	10.1	4.4

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6
Mass of Mold and Soil, g	6085.0	6158.0	6204.0	6155.0		
Mass of Wet Sample & Tare, g	528.8	530.7	620.4	601.2		
Mass of Dry Sample & Tare, g	489.0	483.5	554.6	538.7		
Mass of Tare, g	130.0	129.0	128.8	183.3		
Moisture Content, %	11.1	13.3	15.5	17.6		
Wet Density, pcf	124.0	128.9	131.9	128.7		
Dry Density, pcf	111.7	113.7	114.3	109.4		

Mold ID Number	314
Mass of Mold, g	4211.3
Volume of Mold, ft <sup>3</sup>	0.0333
Hammer ID Number	318
Number of Blows per layer	25
Number of Layers	3



Maximum Dry Density, pcf	114.5	Optimum Moisture Content, %	14.8
Absorption, % (assumed)	2	Corrected Maximum Dry Density, pcf	119.0
Corrected Maximum Dry Density, pcf	119.0	Corrected Optimum Moisture Content, %	12.5

USCS (ASTM D2487; D2488)

NA

DESCRIPTION

NA

AASHTO (M 145)

NA

Class Sub-class

GA DOT

NA NA





**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	RI
Date	04/02/15
Checked By	<i>RI</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19740/B-3	Depth/Elev.	0-8'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	114.5
Optimum Moisture Content (O.M.C.), %	14.8

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	14.8

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1148.97

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	533.10	541.60
Mass of Dry Soil and Tare, g	515.90	484.90
Mass of Tare, g	128.60	95.40
Moisture Content, %	4.4	14.6
<b>Water Adjustment, g</b>	119.0	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.128	Swell, %	9.17
Final Dial Gage Reading, inch	0.220	Swell Mold ID #	229
Change in Dial Gage Readings, inch	0.092	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height			
Initial Dial Gage Reading, inch	0.747	Diameter	Original Volume, in <sup>3</sup>	12.53
Final Dial Gage Reading, inch	0.746	0.729	Final Volume, in <sup>3</sup>	12.39
Preset Dial Gage Gap, inch	0.250	3.250	Shrinkage, %	1.15
Dial Gage ID #	360	359	Shrink Mold ID #	201
Stand ID #	55	177		

Proctor Dry Density (Minus No. 10 Material), pcf	114.5
% Retained on No. 10 Sieve	18.6
Conversion Factor	0.835

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>10.3</b>	<b>8.6</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/01/15**

Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19740/B-3	Depth/Elev.	0-8'
Location	-	Add. Info	-

**GDT-4**


**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	345.4	Mass of Wet Sample & Tare, g	533.10
Mass of Dry Sample & Tare, g	323.0	Mass of Dry Sample & Tare, g	515.90
Mass of Tare, g	101.3	Mass of Tare, g	128.60
Moisture Content, %	10.1	Moisture Content, %	4.4
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	17826.1	Mass of Air-Dried Fine Material & Tare, g	52.23
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	17068.1	Mass of Dry Fine Material, g	50.01
		% of Total Sample Passing No. 10 Sieve	81.4

**SIEVE ANALYSIS**

<b>GRADATION OF PLUS NO.10 Material</b>				<b>GRADATION OF MINUS NO.10 Material</b>						
Mass of Tare, g	0.0			Mass of Tare, g	0.0					
Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing
1.5"	0.0	0.0	0.0	100.0	#40	10.84	10.84	21.7	78.3	63.8
.75"	104.3	104.3	0.6	99.4	#60	15.22	15.22	30.4	69.6	56.6
#10	3171.8	3171.8	18.6	81.4	#200	28.28	28.28	56.5	43.5	35.4
					Total	41.12	41.12	82.2	-	
					Clay (Effluent)				17.8	14.5

**Particle Size Distribution**



Class	Sub-class
GA DOT <b>NA</b>	<b>NA</b>

<b>Soil Classification (AASHTO M-145)</b>	
% Gravel	18.6
% COARSE Sand	17.6
% FINE Sand	28.4
% FINES (Silt-Clay)	35.4
% Clay	14.5
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
<b>NA</b>	<b>NA</b>	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

RI

Date

04/01/15

Checked By

18

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19741/B-4
Location	-

Lab. PR. #	1595-02-1
S. Type	Bulk
Depth/Elev.	0-6'
Add. Info	-

**GDT-7**

**Method of Test for Determining Maximum Density of Soils**

**SAMPLE DATA**

	Air-Dried	Oven-Dried*
Total Mass of Soil before sieving, g	20051.0	18998.8
Mass of Mat. retained on No.10 sieve, g		4767.1
Material Retained on No.10 sieve, %		25.1

Note: Values based on calculated oven-dried mass

**MOISTURE CONTENT**


	Natural	Air-Dry Material
Mass of Wet Sample & Tare, g	326.40	509.10
Mass of Dry Sample & Tare, g	298.00	487.60
Mass of Tare, g	93.60	99.40
Moisture Content, %	13.9	5.5

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6
Mass of Mold and Soil, g	6090.0	6160.0	6195.0	6140.0		
Mass of Wet Sample & Tare, g	601.0	612.8	615.3	592.8		
Mass of Dry Sample & Tare, g	553.8	558.3	552.8	518.3		
Mass of Tare, g	174.8	184.0	178.3	124.2		
Moisture Content, %	12.5	14.6	16.7	18.9		
Wet Density, pcf	124.4	129.0	131.3	127.7		
Dry Density, pcf	110.6	112.6	112.5	107.4		

Mold ID Number	314
Mass of Mold, g	4211.3
Volume of Mold, ft <sup>3</sup>	0.0333
Hammer ID Number	318
Number of Blows per layer	25
Number of Layers	3



Maximum Dry Density, pcf	113.0	Optimum Moisture Content, %	15.7
Absorption, % (assumed)	2	Corrected Maximum Dry Density, pcf	119.3
		Corrected Optimum Moisture Content, %	12.5

USCS (ASTM D2487; D2488)

NA

DESCRIPTION

NA

AASHTO (M 145)

NA

Class Sub-class

GA DOT

NA NA



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	RI
Date	04/02/15
Checked By	<i>RB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19741/B-4	Depth/Elev.	0-6'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	113.0
Optimum Moisture Content (O.M.C.), %	15.7

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	15.7

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1137.03

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	509.10	545.20
Mass of Dry Soil and Tare, g	487.60	484.90
Mass of Tare, g	99.40	98.50
Moisture Content, %	5.5	15.6
<b>Water Adjustment, g</b>	115.5	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.129	Swell, %	6.57
Final Dial Gage Reading, inch	0.195	Swell Mold ID #	226
Change in Dial Gage Readings, inch	0.066	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height			
Initial Dial Gage Reading, inch	0.745	Diameter	Original Volume, in <sup>3</sup>	12.50
Final Dial Gage Reading, inch	0.742	0.727	Final Volume, in <sup>3</sup>	12.32
Preset Dial Gage Gap, inch	0.250	3.250	Shrinkage, %	1.44
Dial Gage ID #	360	359	Shrink Mold ID #	201
Stand ID #	55	177		

Proctor Dry Density (Minus No. 10 Material), pcf	113.0
% Retained on No. 10 Sieve	25.1
Conversion Factor	0.783

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>8.0</b>	<b>6.3</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/01/15**

Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19741/B-4	Depth/Elev.	0-6'
Location	-	Add. Info	-

**GDT-4**

**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	326.4	Mass of Wet Sample & Tare, g	509.10
Mass of Dry Sample & Tare, g	298.0	Mass of Dry Sample & Tare, g	487.60
Mass of Tare, g	93.6	Mass of Tare, g	99.40
Moisture Content, %	13.9	Moisture Content, %	5.5
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	20051.0	Mass of Air-Dried Fine Material & Tare, g	52.78
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	18998.8	Mass of Dry Fine Material, g	50.01
		% of Total Sample Passing No. 10 Sieve	74.9


**SIEVE ANALYSIS**

**GRADATION OF PLUS NO.10 Material**

**GRADATION OF MINUS NO.10 Material**

Mass of Tare, g	0.0	Mass of Tare, g	0.0																																																									
<table border="1"> <thead> <tr> <th>Sieve Size</th> <th>Accumulative mass of Sample &amp; Tare, g</th> <th>Accumulative mass of Sample, g</th> <th>% RETAINED</th> <th>% PASSING</th> </tr> </thead> <tbody> <tr> <td>1.5"</td> <td>0.0</td> <td>0.0</td> <td>0.0</td> <td>100.0</td> </tr> <tr> <td>.75"</td> <td>377.8</td> <td>377.8</td> <td>2.0</td> <td>98.0</td> </tr> <tr> <td>#10</td> <td>4767.1</td> <td>4767.1</td> <td>25.1</td> <td>74.9</td> </tr> </tbody> </table>		Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	1.5"	0.0	0.0	0.0	100.0	.75"	377.8	377.8	2.0	98.0	#10	4767.1	4767.1	25.1	74.9	<table border="1"> <thead> <tr> <th>Sieve Size</th> <th>Accumulative mass of Sample &amp; Tare, g</th> <th>Accumulative mass of Sample, g</th> <th>% RETAINED</th> <th>% PASSING</th> <th>Adjusted for Total % Passing</th> </tr> </thead> <tbody> <tr> <td>#40</td> <td>12.29</td> <td>12.29</td> <td>24.6</td> <td>75.4</td> <td>56.5</td> </tr> <tr> <td>#60</td> <td>17.53</td> <td>17.53</td> <td>35.1</td> <td>64.9</td> <td>48.7</td> </tr> <tr> <td>#200</td> <td>31.19</td> <td>31.19</td> <td>62.4</td> <td>37.6</td> <td>28.2</td> </tr> <tr> <td>Total</td> <td>42.06</td> <td>42.06</td> <td>84.1</td> <td>-</td> <td></td> </tr> <tr> <td>Clay (Effluent)</td> <td></td> <td></td> <td>15.9</td> <td>11.9</td> <td></td> </tr> </tbody> </table>			Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing	#40	12.29	12.29	24.6	75.4	56.5	#60	17.53	17.53	35.1	64.9	48.7	#200	31.19	31.19	62.4	37.6	28.2	Total	42.06	42.06	84.1	-		Clay (Effluent)			15.9	11.9	
Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING																																																								
1.5"	0.0	0.0	0.0	100.0																																																								
.75"	377.8	377.8	2.0	98.0																																																								
#10	4767.1	4767.1	25.1	74.9																																																								
Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing																																																							
#40	12.29	12.29	24.6	75.4	56.5																																																							
#60	17.53	17.53	35.1	64.9	48.7																																																							
#200	31.19	31.19	62.4	37.6	28.2																																																							
Total	42.06	42.06	84.1	-																																																								
Clay (Effluent)			15.9	11.9																																																								

**Particle Size Distribution**



GA DOT	Class	Sub-class
	NA	NA

Soil Classification (AASHTO M-145)	
% Gravel	25.1
% COARSE Sand	18.4
% FINE Sand	28.3
% FINES (Silt-Clay)	28.2
% Clay	11.9
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
NA	NA	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

RI

Date

04/01/15

Checked By

18

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19742/B-5
Location	-

Lab. PR. #	1595-02-1
S. Type	Bulk
Depth/Elev.	0-13'
Add. Info	-

**GDT-7**

**Method of Test for Determining Maximum Density of Soils**

**SAMPLE DATA**

	Air-Dried	Oven-Dried*
Total Mass of Soil before sieving, g	17621.0	16427.8
Mass of Mat. retained on No.10 sieve, g		2234.2
Material Retained on No.10 sieve, %		13.6

Note: Values based on calculated oven-dried mass

**MOISTURE CONTENT**


	Natural	Air-Dry Material
Mass of Wet Sample & Tare, g	307.90	496.80
Mass of Dry Sample & Tare, g	277.50	469.30
Mass of Tare, g	91.20	90.70
Moisture Content, %	16.3	7.3

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6
Mass of Mold and Soil, g	6130.0	6190.0	6207.0	6163.0		
Mass of Wet Sample & Tare, g	535.2	553.3	540.2	551.1		
Mass of Dry Sample & Tare, g	484.8	497.5	482.6	483.9		
Mass of Tare, g	125.9	127.9	130.0	125.1		
Moisture Content, %	14.0	15.1	16.3	18.7		
Wet Density, pcf	127.0	131.0	132.1	129.2		
Dry Density, pcf	111.4	113.8	113.6	108.8		

Mold ID Number	314
Mass of Mold, g	4211.3
Volume of Mold, ft <sup>3</sup>	0.0333
Hammer ID Number	318
Number of Blows per layer	25
Number of Layers	3



Maximum Dry Density, pcf	114.1	Optimum Moisture Content, %	15.6
Absorption, % (assumed)	2	Corrected Maximum Dry Density, pcf	117.5
		Corrected Optimum Moisture Content, %	14.0

USCS (ASTM D2487; D2488)	NA	DESCRIPTION NA
AASHTO (M 145)	NA	
GA DOT	Class: NA, Sub-class: NA	



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	RI
Date	04/02/15
Checked By	<i>RB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19742/B-5	Depth/Elev.	0-13'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	114.1
Optimum Moisture Content (O.M.C.), %	15.6

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	15.6

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1118.74

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	496.80	537.20
Mass of Dry Soil and Tare, g	469.30	480.10
Mass of Tare, g	90.70	112.50
Moisture Content, %	7.3	15.5
<b>Water Adjustment, g</b>	<b>93.3</b>	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.120	Swell, %	7.54
Final Dial Gage Reading, inch	0.195	Swell Mold ID #	230
Change in Dial Gage Readings, inch	0.075	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height			
Initial Dial Gage Reading, inch	0.750	Diameter	Original Volume, in <sup>3</sup>	12.57
Final Dial Gage Reading, inch	0.734	0.712	Final Volume, in <sup>3</sup>	12.13
Preset Dial Gage Gap, inch	0.250	3.250	Shrinkage, %	3.46
Dial Gage ID #	360	359	Shrink Mold ID #	201
Stand ID #	55	177		

Proctor Dry Density (Minus No. 10 Material), pcf	114.1
% Retained on No. 10 Sieve	13.6
Conversion Factor	0.879

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>11.0</b>	<b>9.7</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/01/15**

Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19742/B-5	Depth/Elev.	0-13'
Location	-	Add. Info	-

**GDT-4**

**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	307.9	Mass of Wet Sample & Tare, g	496.80
Mass of Dry Sample & Tare, g	277.5	Mass of Dry Sample & Tare, g	469.30
Mass of Tare, g	91.2	Mass of Tare, g	90.70
Moisture Content, %	16.3	Moisture Content, %	7.3
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	17621.0	Mass of Air-Dried Fine Material & Tare, g	53.64
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	16427.8	Mass of Dry Fine Material, g	50.01
		% of Total Sample Passing No. 10 Sieve	86.4


**SIEVE ANALYSIS**

**GRADATION OF PLUS NO.10 Material**

**GRADATION OF MINUS NO.10 Material**

Mass of Tare, g	0.0	Mass of Tare, g	0.0							
Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing		
Sieve Size				Sieve Size						
1.5"	0.0	0.0	0.0	100.0	#40	9.09	9.09	18.2	81.8	70.7
.75"	55.4	55.4	0.3	99.7	#60	13.32	13.32	26.6	73.4	63.4
#10	2234.2	2234.2	13.6	86.4	#200	25.54	25.54	51.1	48.9	42.3
					Total	37.69	37.69	75.4	-	
					Clay (Effluent)				24.6	21.3

**Particle Size Distribution**



Class	Sub-class
GA DOT	NA NA

Soil Classification (AASHTO M-145)	
% Gravel	13.6
% COARSE Sand	15.7
% FINE Sand	28.4
% FINES (Silt-Clay)	42.3
% Clay	21.3
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
NA	NA	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130





**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

RI

Date

04/01/15

Checked By

18

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19743/B-6
Location	-

Lab. PR. #	1595-02-1
S. Type	Bulk
Depth/Elev.	0-16'
Add. Info	-

**GDT-7**

**Method of Test for Determining Maximum Density of Soils**

**SAMPLE DATA**

	Air-Dried	Oven-Dried*
Total Mass of Soil before sieving, g	16500.0	15263.2
Mass of Mat. retained on No.10 sieve, g		2575.1
Material Retained on No.10 sieve, %		16.9

Note: Values based on calculated oven-dried mass

**MOISTURE CONTENT**


	Natural	Air-Dry Material
Mass of Wet Sample & Tare, g	523.40	502.50
Mass of Dry Sample & Tare, g	463.70	472.00
Mass of Tare, g	95.00	95.60
Moisture Content, %	16.2	8.1

**REMARKS**

**TEST DATA**

Points	1	2	3	4	5	6
Mass of Mold and Soil, g	6123.0	6165.0	6174.0	6126.0		
Mass of Wet Sample & Tare, g	522.8	540.2	535.0	555.1		
Mass of Dry Sample & Tare, g	470.9	483.7	475.9	485.6		
Mass of Tare, g	124.6	124.5	129.6	128.8		
Moisture Content, %	15.0	15.7	17.1	19.5		
Wet Density, pcf	126.6	129.3	129.9	126.8		
Dry Density, pcf	110.1	111.8	111.0	106.1		

Mold ID Number	314
Mass of Mold, g	4211.3
Volume of Mold, ft <sup>3</sup>	0.0333
Hammer ID Number	318
Number of Blows per layer	25
Number of Layers	3



Maximum Dry Density, pcf	112.0	Optimum Moisture Content, %	16.1
Absorption, % (assumed)	2	Corrected Maximum Dry Density, pcf	116.4
		Corrected Optimum Moisture Content, %	13.6

USCS (ASTM D2487; D2488)	NA	DESCRIPTION	NA
AASHTO (M 145)	NA		
GA DOT	Class: NA, Sub-class: NA		



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	RI
Date	04/02/15
Checked By	<i>RB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19743/B-6	Depth/Elev.	0-16'
Location	-	Add. Info	-

**GDT- 6**

**Method of Test for Determining Volume Change of Soil**

**SAMPLE PREPARATION (Material passing No.10 Sieve )**

**Proctor Data (GDT- 7 or GDT- 67)**

Maximum Dry Density, pcf	112.0
Optimum Moisture Content (O.M.C.), %	16.1

**Moisture Content Requirements**

Difference from O.M.C., %	0.0
Target Moisture Content, %	16.1

**Soil Preparation**

Mass of Wet Soil and Bag, g	1200.00
Mass of Bag, g	0.00
Mass of Wet Soil, g	1200.00
Mass of Dry Soil, g	1110.05

**Moisture Content**

**Before Adjustment**

**After Adjustment**

Mass of Wet Soil and Tare, g	502.50	539.20
Mass of Dry Soil and Tare, g	472.00	478.40
Mass of Tare, g	95.60	100.50
Moisture Content, %	8.1	16.1
<b>Water Adjustment, g</b>	<b>88.8</b>	

**SWELL TESTING**

Initial Dial Gage Reading, inch	0.126	Swell, %	<b>13.39</b>
Final Dial Gage Reading, inch	0.260	Swell Mold ID #	227
Change in Dial Gage Readings, inch	0.134	Dial Gage ID #	105
Preset Dial Gage Gap, inch	0.875		

**SHRINKAGE TESTING**

	Height		Diameter	Original Volume, in <sup>3</sup>	12.55
Initial Dial Gage Reading, inch	0.749		0.727	Final Volume, in <sup>3</sup>	12.25
Final Dial Gage Reading, inch	0.736		3.250	Shrinkage, %	<b>2.43</b>
Preset Dial Gage Gap, inch	0.250		359	Shrink Mold ID #	201
Dial Gage ID #	360		177		
Stand ID #	55				

Proctor Dry Density (Minus No. 10 Material), pcf	112.0
% Retained on No. 10 Sieve	16.9
Conversion Factor	0.855

	Minus No.10 Soil	Composite Soil
<b>TOTAL VOLUME CHANGE, %</b>	<b>15.8</b>	<b>13.5</b>



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By **RI**

Date **04/01/15**

Checked By **IB**

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Bulk
Sample ID	19743/B-6	Depth/Elev.	0-16'
Location	-	Add. Info	-

**GDT-4**


**Method of Test for Determining Gradation of Soil**

<b>NATURAL MOISTURE CONTENT</b>		<b>MOISTURE CONTENT of AIR-DRIED MATERIAL (Minus No. 10 Sieve)</b>	
Mass of Wet Sample & Tare, g	523.4	Mass of Wet Sample & Tare, g	502.50
Mass of Dry Sample & Tare, g	463.7	Mass of Dry Sample & Tare, g	472.00
Mass of Tare, g	95.0	Mass of Tare, g	95.60
Moisture Content, %	16.2	Moisture Content, %	8.1
<b>TOTAL SAMPLE</b>		<b>FINE PORTION of MATERIAL USED for SIEVE</b>	
Total mass of air-dried sample before sieving on No.10 & tare, g	16500.0	Mass of Air-Dried Fine Material & Tare, g	54.06
Mass of Tare, g	0.0	Mass of Tare, g	0.00
Total Mass of dry sample, g	15263.2	Mass of Dry Fine Material, g	50.01
		% of Total Sample Passing No. 10 Sieve	83.1

**SIEVE ANALYSIS**

<b>GRADATION OF PLUS NO.10 Material</b>				<b>GRADATION OF MINUS NO.10 Material</b>						
Mass of Tare, g	0.0			Mass of Tare, g	0.0					
Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Sieve Size	Accumulative mass of Sample & Tare, g	Accumulative mass of Sample, g	% RETAINED	% PASSING	Adjusted for Total % Passing
1.5"	0.0	0.0	0.0	100.0	#40	12.48	12.48	25.0	75.0	62.4
.75"	77.4	77.4	0.5	99.5	#60	17.56	17.56	35.1	64.9	53.9
#10	2575.1	2575.1	16.9	83.1	#200	30.00	30.00	60.0	40.0	33.3
					Total	41.71	41.71	83.4	-	
					Clay (Effluent)				16.6	13.8

**Particle Size Distribution**



Class	Sub-class
GA DOT <b>NA</b>	<b>NA</b>

<b>Soil Classification (AASHTO M-145)</b>	
% Gravel	16.9
% COARSE Sand	20.7
% FINE Sand	29.1
% FINES (Silt-Clay)	33.3
% Clay	13.8
% TOTAL SAMPLE	100.0

DESCRIPTION	REMARKS
NA	

USCS (ASTM D2487; D2488)	AASHTO (M 145)	Oven ID #	12/14/2015
<b>NA</b>	<b>NA</b>	Balance ID#	1/6/7
		Sieve Shaker ID #	54/130



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

NK

Date

02/11/00

Checked By


*LB*

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19744/B-1D	Depth/Elev.	18.5-20'
Location	-	Add. Info	-

**ASTM D 4318/AASHTO T 88, T 89**

**Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils (Atterberg Limits)**

	LIQUID LIMIT			
	34	27	18	
Number of Blows				
Mass of Wet Sample & Tare, g	42.37	43.32	46.91	Oven ID # 12/13/14/15
Mass of Dry Sample & Tare, g	38.39	39.22	42.53	Balance ID # 2
Mass of Tare, g	24.71	25.57	28.70	Liquid Limit Device ID # 56
Moisture Content, %	29.09	30.04	31.67	



	PLASTIC LIMIT		
Mass of Wet Sample & Tare, g	35.47	32.55	PREPARATION PROCEDURE <input type="text" value="DRY"/>
Mass of Dry Sample & Tare, g	32.79	30.91	NOTE: MATERIAL PASSING NO. 40 SIEVE WAS USED FOR TEST
Mass of Tare, g	22.82	24.73	
Moisture Content, %	26.88	26.54	

	NATURAL MOISTURE		
Mass of Wet Sample & Tare, g	242.90		LIQUID LIMIT (LL) <input type="text" value="30"/>
Mass of Dry Sample & Tare, g	230.10		PLASTIC LIMIT (PL) <input type="text" value="27"/>
Mass of Tare, g	139.40		PLASTICITY INDEX (PI) <input type="text" value="3"/>
Moisture Content, %	14.11		LIQUIDITY INDEX (LI) <input type="text" value="-4.30"/>

DESCRIPTION

USCS (ASTM D2487; D2488)  AASHTO (M 145)



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	AV
Date	03/26/15
Checked By	<i>IB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19744/B-1D	Depth/Elev.	18.5-20'
Location	-	Add. Info	-

**ASTM D 422/AASHTO T 88**

**Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)**

<i>As-Received Moisture Content</i>		<i>Moisture Content of Material Used for Hydrometer Analysis</i>	
Mass of Wet Sample & Tare, g	242.90	Mass of Wet Sample & Tare, g	242.90
Mass of Dry Sample & Tare, g	230.10	Mass of Dry Sample & Tare, g	230.10
Mass of Tare, g	139.40	Mass of Tare, g	139.40
Moisture Content, %	14.1	Moisture Content, %	14.1
Mass of Total Sample before separation on #4 sieve & Tare, g	556.50	Mass of Sample used for hydrometer analysis, g	81.17
Mass of Tare, g	0.00	Dry Mass, g	71.13
Total Mass of Dry Sample, g	487.68	% of Total Sample passing #4 sieve	88.9

**SIEVE ANALYSIS**

<i>PORION OF SAMPLE RETAINED ON #4 SIEVE</i>				<i>PORION OF SAMPLE PASSING #4 SIEVE (Hydrometer Backsieve)</i>			
Mass of Tare, g	0.00						
Sieve Size	Sample & Tare, g	% RETAINED	%PASSING	Sieve Size	Cumulative Mass retained, g	% PASSING	
12"	COBBLES	0.0	100.0	#10	MEDIUM SAND	5.55	82.0
3"		0.0	100.0	#20	SAND	13.44	72.1
2.5"	COARSE GRAVEL	0.0	100.0	#40		23.17	60.0
2"		0.0	100.0	#60	FINE SAND	31.52	49.5
1.5"		0.0	100.0	#100		40.36	38.5
1"		0.0	100.0	#200	FINES	50.61	25.7
.75"		0.00	0.0	Remarks			
.5"	FINE GRAVEL	17.27	3.5				
.375"		27.50	5.6				
#4	COARSE SAND	53.94	11.1				

<b>HYDROMETER ANALYSIS</b>				<b>PARTICLE-SIZE ANALYSIS</b>			
Length of Dispersion Period	1 Minute			% COBBLES	0.0	% MEDIUM SAND	22.0
Mechanical Dispersion Device ID #	61			% COARSE GRAVEL	0.0	% FINE SAND	34.3
Amount of Dispersing Agent (ml)	125.0			% FINE GRAVEL	11.1	% FINES	25.7
Specific Gravity (assumed)	2.700			% COARSE SAND	6.9	% TOTAL SAMPLE	100.0
Specific Gravity (tested)				% CLAY(<0.005mm)	7.6	% CLAY(<0.002mm)	5.3
Starting time	13:28						

Date	Time	Testing time (min)	Reading	Temp (°C)	K	Composite Correction	Actual Reading	Effective Depth (cm)	a	Particle Diam. (mm)	Percent Passing
04/01/15	13:30	2	21.0	19.2	0.01361	5.0	16.0	13.7	0.99	0.0357	19.8
04/01/15	13:33	5	18.0	19.2	0.01361	5.0	13.0	14.2	0.99	0.0230	16.1
04/01/15	13:43	15	15.0	19.2	0.01361	5.0	10.0	14.7	0.99	0.0135	12.4
04/01/15	13:58	30	14.0	19.2	0.01361	5.0	9.0	14.9	0.99	0.0096	11.1
04/01/15	14:28	60	12.5	19.2	0.01361	5.0	7.5	15.1	0.99	0.0068	9.3
04/01/15	17:38	250	10.0	19.2	0.01361	5.0	5.0	15.6	0.99	0.0034	6.2
04/02/15	13:28	1440	9.0	19.2	0.01361	5.0	4.0	15.7	0.99	0.0014	5.0

Hydrometer 152H ID # 451190  
Sieve Shaker ID # 54/130

Oven ID # 12/13/14/15  
Balance ID# 1/6/7



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By AV

Date 03/26/15

Checked By *LB*


Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19744/B-1D
Location	-

Lab. PR. #	1595-02-1
S. Type	Jar
Depth/Elev.	18.5-20'
Add. Info	-

**ASTM D 422/AASHTO T 88**

Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)

**Particle-Size Analysis**



Boulders	Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt or Clay
		Gravel		Sand			

DESCRIPTION: Dark Yellowish Brown Silty Sand

D <sub>10</sub>	NA	mm
D <sub>30</sub>	NA	mm
D <sub>60</sub>	NA	mm
Cu	NA	
Cc	NA	

USCS (ASTM D2487; D2488)

SM



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

NK

Date

03/31/15

Checked By

*LB*


Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19745/B-5	Depth/Elev.	8.5-10'
Location	-	Add. Info	-

**ASTM D 4318/AASHTO T 88, T 89**

**Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils (Atterberg Limits)**

	LIQUID LIMIT		
Number of Blows	33	23	19
Mass of Wet Sample & Tare, g	47.45	43.50	44.45
Mass of Dry Sample & Tare, g	42.93	39.58	39.14
Mass of Tare, g	28.61	28.21	24.31
Moisture Content, %	31.56	34.48	35.81

Oven ID #	12/13/14/15
Balance ID #	2
Liquid Limit Device ID #	56



	PLASTIC LIMIT	
Mass of Wet Sample & Tare, g	29.87	34.82
Mass of Dry Sample & Tare, g	27.84	32.41
Mass of Tare, g	20.75	23.92
Moisture Content, %	28.63	28.39

PREPARATION PROCEDURE

NOTE: MATERIAL PASSING NO. 40 SIEVE WAS USED FOR TEST

	NATURAL MOISTURE
Mass of Wet Sample & Tare, g	226.10
Mass of Dry Sample & Tare, g	209.50
Mass of Tare, g	100.90
Moisture Content, %	15.29

LIQUID LIMIT (LL)	34
PLASTIC LIMIT (PL)	29
PLASTICITY INDEX (PI)	5
LIQUIDITY INDEX (LI)	-2.74

DESCRIPTION

USCS (ASTM D2487; D2488)

AASHTO (M 145)



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	AV
Date	03/26/15
Checked By	<i>LB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19745/B-5	Depth/Elev.	8.5-10'
Location	-	Add. Info	-

**ASTM D 422/AASHTO T 88**

**Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)**

<i>As-Received Moisture Content</i>		<i>Moisture Content of Material Used for Hydrometer Analysis</i>	
Mass of Wet Sample & Tare, g	226.10	Mass of Wet Sample & Tare, g	226.10
Mass of Dry Sample & Tare, g	209.50	Mass of Dry Sample & Tare, g	209.50
Mass of Tare, g	100.90	Mass of Tare, g	100.90
Moisture Content, %	15.3	Moisture Content, %	15.3
Mass of Total Sample before separation on #4 sieve & Tare, g	515.10	Mass of Sample used for hydrometer analysis, g	78.15
Mass of Tare, g	0.00	Dry Mass, g	67.79
Total Mass of Dry Sample, g	446.80	% of Total Sample passing #4 sieve	93.7

**SIEVE ANALYSIS**

<i>PORTION OF SAMPLE RETAINED ON #4 SIEVE</i>				<i>PORTION OF SAMPLE PASSING #4 SIEVE (Hydrometer Backsieve)</i>			
Mass of Tare, g	0.00						
Sieve Size	Sample & Tare, g	% RETAINED	% PASSING	Sieve Size	Cumulative Mass retained, g	% PASSING	
12"	COBBLES	0.0	100.0	#10	MEDIUM SAND	6.00	85.4
3"		0.0	100.0	#20	SAND	13.85	74.5
2.5"	COARSE GRAVEL	0.0	100.0	#40		22.43	62.7
2"		0.0	100.0	#60	FINE SAND	29.16	53.4
1.5"		0.0	100.0	#100		36.23	43.6
1"		0.0	100.0	#200	FINES	44.59	32.1
.75"		0.00	0.0	Remarks			
.5"	FINE GRAVEL	9.40	2.1				
.375"		11.05	2.5				
#4	COARSE SAND	28.32	6.3				

<b>HYDROMETER ANALYSIS</b>			<b>PARTICLE-SIZE ANALYSIS</b>			
Length of Dispersion Period	1 Minute		% COBBLES	0.0	% MEDIUM SAND	22.7
Mechanical Dispersion Device ID #	61		% COARSE GRAVEL	0.0	% FINE SAND	30.6
Amount of Dispersing Agent (ml)	125.0		% FINE GRAVEL	6.3	% FINES	32.1
Specific Gravity (assumed)	2.700		% COARSE SAND	8.3	% TOTAL SAMPLE	100.0
Specific Gravity (tested)			% CLAY(<0.005mm)	16.8	% CLAY(<0.002mm)	10.6
Starting time	13:30					

Date	Time	Testing time (min)	Reading	Temp (°C)	K	Composite Correction	Actual Reading	Effective Depth (cm)	a	Particle Diam. (mm)	Percent Passing
04/01/15	13:32	2	25.0	19.2	0.01361	5.0	20.0	13.1	0.99	0.0348	27.4
04/01/15	13:35	5	23.0	19.2	0.01361	5.0	18.0	13.4	0.99	0.0223	24.6
04/01/15	13:45	15	20.5	19.2	0.01361	5.0	15.5	13.8	0.99	0.0131	21.2
04/01/15	14:00	30	19.5	19.2	0.01361	5.0	14.5	14.0	0.99	0.0093	19.8
04/01/15	14:30	60	18.0	19.2	0.01361	5.0	13.0	14.2	0.99	0.0066	17.8
04/01/15	17:40	250	16.5	19.2	0.01361	5.0	11.5	14.5	0.99	0.0033	15.7
04/02/15	13:30	1440	11.0	19.2	0.01361	5.0	6.0	15.4	0.99	0.0014	8.2

Hydrometer 152H ID #   
Sieve Shaker ID #

Oven ID #   
Balance ID#





**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)




Tested By	AV
Date	03/26/15
Checked By	<i>IB</i>

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19745/B-5
Location	-

Lab. PR. #	1595-02-1
S. Type	Jar
Depth/Elev.	8.5-10'
Add. Info	-

**ASTM D 422/AASHTO T 88  
Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)**

### Particle-Size Analysis



Boulders	Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt or Clay
		Gravel		Sand			

DESCRIPTION: Reddish Brown Silty Sand

D <sub>10</sub>	NA	mm
D <sub>30</sub>	NA	mm
D <sub>60</sub>	NA	mm
C <sub>u</sub>	NA	
C <sub>c</sub>	NA	

USCS (ASTM D2487; D2488) SM



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By

NK

Date

03/31/15

Checked By


*LB*

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19746/B-6	Depth/Elev.	8.5-10'
Location	-	Add. Info	-

**ASTM D 4318/AASHTO T 88, T 89**

**Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils (Atterberg Limits)**

	LIQUID LIMIT			
	35	24	17	
Number of Blows				Oven ID #
Mass of Wet Sample & Tare, g	44.15	46.82	43.37	12/13/14/15
Mass of Dry Sample & Tare, g	40.05	41.59	38.15	Balance ID #
Mass of Tare, g	28.50	27.86	25.20	2
Moisture Content, %	35.50	38.09	40.31	Liquid Limit Device ID #
				56



	PLASTIC LIMIT		
Mass of Wet Sample & Tare, g	32.56	34.93	PREPARATION PROCEDURE
Mass of Dry Sample & Tare, g	30.23	32.27	DRY
Mass of Tare, g	23.32	24.37	NOTE: MATERIAL PASSING NO. 40 SIEVE WAS USED FOR TEST
Moisture Content, %	33.72	33.67	

	NATURAL MOISTURE	
Mass of Wet Sample & Tare, g	266.30	LIQUID LIMIT (LL)
Mass of Dry Sample & Tare, g	240.20	38
Mass of Tare, g	137.80	PLASTIC LIMIT (PL)
Moisture Content, %	25.49	34
		PLASTICITY INDEX (PI)
		4
		LIQUIDITY INDEX (LI)
		-2.13

DESCRIPTION Yellowish Brown Silty Sand

USCS (ASTM D2487; D2488) SM AASHTO (M 145) NA



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)



Tested By	AV
Date	03/26/15
Checked By	<i>IB</i>

Client Pr. #	150411-007	Lab. PR. #	1595-02-1
Pr. Name	Sun Valley Drive Extension	S. Type	Jar
Sample ID	19746/B-6	Depth/Elev.	8.5-10'
Location	-	Add. Info	-

**ASTM D 422/AASHTO T 88**

**Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)**

As-Received Moisture Content		Moisture Content of Material Used for Hydrometer Analysis	
Mass of Wet Sample & Tare, g	266.30	Mass of Wet Sample & Tare, g	266.30
Mass of Dry Sample & Tare, g	240.20	Mass of Dry Sample & Tare, g	240.20
Mass of Tare, g	137.80	Mass of Tare, g	137.80
Moisture Content, %	25.5	Moisture Content, %	25.5
Mass of Total Sample before separation on #4 sieve & Tare, g	531.40	Mass of Sample used for hydrometer analysis, g	79.69
Mass of Tare, g	0.00	Dry Mass, g	63.50
Total Mass of Dry Sample, g	423.47	% of Total Sample passing #4 sieve	99.9

**SIEVE ANALYSIS**

PORTION OF SAMPLE RETAINED ON #4 SIEVE				PORTION OF SAMPLE PASSING #4 SIEVE (Hydrometer Backsieve)			
Mass of Tare, g	0.00						
Sieve Size	Sample & Tare, g	% RETAINED	% PASSING	Sieve Size	Mass retained, g	% PASSING	
12"	COBBLES	0.0	100.0	#10	MEDIUM SAND	2.73	95.7
3"		0.0	100.0	#20	SAND	5.53	91.2
2.5"	COARSE GRAVEL	0.0	100.0	#40		10.48	83.5
2"		0.0	100.0	#60	FINE SAND	17.28	72.8
1.5"		0.0	100.0	#100		26.19	58.7
1"		0.0	100.0	#200	FINES	37.03	41.7
.75"	FINE GRAVEL	0.0	100.0	Remarks			
.5"		0.0	100.0				
.375"		0.00	100.0				
#4	COARSE SAND	0.22	99.9				

HYDROMETER ANALYSIS		PARTICLE-SIZE ANALYSIS			
Length of Dispersion Period	1 Minute	% COBBLES	0.0	% MEDIUM SAND	12.2
Mechanical Dispersion Device ID #	61	% COARSE GRAVEL	0.0	% FINE SAND	41.8
Amount of Dispersing Agent (ml)	125.0	% FINE GRAVEL	0.1	% FINES	41.7
Specific Gravity (assumed)	2.700	% COARSE SAND	4.3	% TOTAL SAMPLE	100.0
Specific Gravity (tested)		% CLAY(<0.005mm)	11.2	% CLAY(<0.002mm)	8.3
Starting time	13:32				

Date	Time	Testing time (min)	Reading	Temp (°C)	K	Composite Correction	Actual Reading	Effective Depth (cm)	a	Particle Diam. (mm)	Percent Passing
04/01/15	13:34	2	26.0	19.2	0.01361	5.0	21.0	12.9	0.99	0.0346	32.7
04/01/15	13:37	5	22.0	19.2	0.01361	5.0	17.0	13.6	0.99	0.0224	26.5
04/01/15	13:47	15	18.0	19.2	0.01361	5.0	13.0	14.2	0.99	0.0133	20.3
04/01/15	14:02	30	16.0	19.2	0.01361	5.0	11.0	14.6	0.99	0.0095	17.1
04/01/15	14:32	60	13.5	19.2	0.01361	5.0	8.5	15.0	0.99	0.0068	13.2
04/01/15	17:42	250	11.0	19.2	0.01361	5.0	6.0	15.4	0.99	0.0034	9.3
04/02/15	13:32	1440	10.0	19.2	0.01361	5.0	5.0	15.6	0.99	0.0014	7.8

Hydrometer 152H ID # 451190  
Sieve Shaker ID # 54/130

Oven ID # 12/13/14/15  
Balance ID# 1/6/7



**TIMELY  
ENGINEERING  
SOIL  
TESTS, LLC**

1874 Forge Street Tucker, GA 30084

Phone: 770-938-8233

Fax: 770-923-8973

Web: [www.test-llc.com](http://www.test-llc.com)




Tested By	AV
Date	03/26/15
Checked By	<i>LB</i>

Client Pr. #	150411-007
Pr. Name	Sun Valley Drive Extension
Sample ID	19746/B-6
Location	-

Lab. PR. #	1595-02-1
S. Type	Jar
Depth/Elev.	8.5-10'
Add. Info	-

**ASTM D 422/AASHTO T 88  
Standard Test Method for Particle-Size Analysis of Soils (with Hydrometer Analysis)**

**Particle-Size Analysis**



Boulders	Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt or Clay
		Gravel		Sand			

DESCRIPTION: Yellowish Brown Silty Sand

D <sub>10</sub>	NA	mm
D <sub>30</sub>	NA	mm
D <sub>60</sub>	NA	mm
Cu	NA	
Cc	NA	

USCS (ASTM D2487; D2488) SM



**ANALYTICAL ENVIRONMENTAL SERVICES, INC.**

April 16, 2015

Sandy Miller  
Ranger Consulting  
3147 Martha Berry Highway  
Rome GA 30165

TEL: (770) 954-1947  
FAX: (770) 954-1947

RE: Sun Valley Dr Ext

Dear Sandy Miller:

Order No: 1504627

Analytical Environmental Services, Inc. received 1 samples on 4/8/2015 1:19:00 PM for the analyses presented in following report.

No problems were encountered during the analyses. Additionally, all results for the associated Quality Control samples were within EPA and/or AES established limits. Any discrepancies associated with the analyses contained herein will be noted and submitted in the form of a project Case Narrative.

AES' certifications are as follows:

- NELAC/Florida Certification number E87582 for analysis of Environmental Water, soil/hazardous waste, and Drinking Water Microbiology, effective 07/01/14-06/30/15.
- AIHA-LAP, LLC Laboratory ID: 100671 for Industrial Hygiene samples (Organics, Inorganics), Environmental Lead (Paint, Soil, Dust Wipes, Air), and Environmental Microbiology (Fungal) Direct Examination, effective until 09/01/15.

These results relate only to the items tested. This report may only be reproduced in full.

If you have any questions regarding these test results, please feel free to call.

Tara Westervelt  
Project Manager



**ANALYTICAL ENVIRONMENTAL SERVICES, INC**

3080 Presidential Drive, Atlanta GA 30340-3704

TEL.: (770) 457-8177 / TOLL-FREE (800) 972-4889 / FAX: (770) 457-8188

**CHAIN OF CUSTODY**

Work Order: 1504627

Date: 8 Apr 2015 Page 1 of 1

COMPANY: <u>Ranger Consulting, Inc.</u>		ADDRESS: <u>3147 Martha Berry Hwy Kome, GA 30165</u>				ANALYSIS REQUESTED						Visit our website <a href="http://www.aesatlanta.com">www.aesatlanta.com</a> to check on the status of your results, place bottle orders, etc.		No # of Containers	
PHONE: <u>678-586-0862</u>		FAX:													
SAMPLED BY: <u>Sandy Miller</u>		SIGNATURE: <u>[Signature]</u>				PRESERVATION (See codes)						REMARKS			
#	SAMPLE ID	DATE	TIME	Grab	Composite										Matrix (See codes)
1	<u>SW-1</u>	<u>8 Apr 2015</u>	<u>1240</u>	<u>X</u>		<u>SW</u>	Resistivity pH NA NA								
2															
3															
4															
5															
6															
7															
8															
9															
10															
11															
12															
13															
14															
RELINQUISHED BY		DATE/TIME		RECEIVED BY		DATE/TIME		PROJECT INFORMATION						RECEIPT	
1: <u>[Signature]</u>		1: <u>8 Apr 2015 1319</u>		1: <u>[Signature]</u>		1: <u>4/8/15 1:19p</u>		PROJECT NAME: <u>Sun Valley Dr Ext</u>						Total # of Containers: <u>1</u>	
2:		2:		2:		2:		PROJECT #: <u>150411-007</u>						Turnaround Time Request	
3:		3:		3:		3:		SITE ADDRESS: <u>Roswell, GA</u>						<input checked="" type="radio"/> Standard 5 Business Days	
								SEND REPORT TO: <u>smiller@rangerconsulting.net</u>						<input type="radio"/> 2 Business Day Rush	
								INVOICE TO: (IF DIFFERENT FROM ABOVE)						<input type="radio"/> Next Business Day Rush	
														<input type="radio"/> Same Day Rush (auth req.)	
														<input type="radio"/> Other	
SPECIAL INSTRUCTIONS/COMMENTS:				SHIPMENT METHOD										STATE PROGRAM (if any):	
				OUT / / VIA:										E-mail? Y/N; Fax? Y/N	
				IN / / VIA:										DATA PACKAGE: I II III IV	
				CLIENT <input checked="" type="radio"/> FedEx UPS MAIL COURIER											
				GROUND OTHER											

SAMPLES RECEIVED AFTER 3PM OR ON SATURDAY ARE CONSIDERED RECEIVED THE NEXT BUSINESS DAY. IF TURNAROUND TIME IS NOT INDICATED, AES WILL PROCEED WITH STANDARD TAT OF SAMPLES. SAMPLES ARE DISPOSED 30 DAYS AFTER REPORT COMPLETION UNLESS OTHER ARRANGEMENTS ARE MADE.

MATRIX CODES: A = Air GW = Groundwater SE = Sediment SO = Soil SW = Surface Water W = Water (Blanks) DW = Drinking Water (Blanks) O = Other (specify) WW = Waste Water  
PRESERVATIVE CODES: H+I = Hydrochloric acid + ice I = Ice only N = Nitric acid S+I = Sulfuric acid + ice S/M+I = Sodium Bisulfate/Methanol + ice O = Other (specify) NA = None

White Copy - Original; Yellow Copy - Client

**Client:** Ranger Consulting  
**Project:** Sun Valley Dr Ext  
**Lab ID:** 1504627

**Case Narrative**

pH Analysis by Method E150.1/SM4500 H+ B:

Sample for pH analysis by Method E150.1/SM4500 H+ B was received and analyzed outside holding time requirement of "immediate or 15 minutes".

**Analytical Environmental Services, Inc**

**Date:** 16-Apr-15

<b>Client:</b> Ranger Consulting	<b>Client Sample ID:</b> SW-1
<b>Project Name:</b> Sun Valley Dr Ext	<b>Collection Date:</b> 4/8/2015 12:40:00 PM
<b>Lab ID:</b> 1504627-001	<b>Matrix:</b> Surface Water

Analyses	Result	Reporting Limit	Qual	Units	BatchID	Dilution Factor	Date Analyzed	Analyst
<b>Resistivity SW9050A</b>								
Resistivity (@100% Moisture Saturation)	18600	0		ohms*cm	R289734	1	04/13/2015 09:00	OM
<b>Hydrogen Ion (pH) by SM4500 H+ B</b>								
pH	6.54	0.0100	H	pH Units	R289596	1	04/10/2015 10:50	JS

<b>Qualifiers:</b>	* Value exceeds maximum contaminant level	E Estimated (value above quantitation range)
	BRL Below reporting limit	S Spike Recovery outside limits due to matrix
	H Holding times for preparation or analysis exceeded	Narr See case narrative
	N Analyte not NELAC certified	NC Not confirmed
	B Analyte detected in the associated method blank	< Less than Result value
	> Greater than Result value	J Estimated value detected below Reporting Limit



Analytical Environmental Services, Inc.

Sample/Cooler Receipt Checklist

Client Ranger Consulting

Work Order Number 1504627

Checklist completed by Katie Forman 4/8/15  
Signature Date

Carrier name: FedEx  UPS  Courier  Client  US Mail  Other

Shipping container/cooler in good condition? Yes  No  Not Present

Custody seals intact on shipping container/cooler? Yes  No  Not Present

Custody seals intact on sample bottles? Yes  No  Not Present

Container/Temp Blank temperature in compliance? (0°≤6°C)\* Yes  No

Cooler #1 3.4°C Cooler #2 \_\_\_\_\_ Cooler #3 \_\_\_\_\_ Cooler #4 \_\_\_\_\_ Cooler #5 \_\_\_\_\_ Cooler #6 \_\_\_\_\_

Chain of custody present? Yes  No

Chain of custody signed when relinquished and received? Yes  No

Chain of custody agrees with sample labels? Yes  No

Samples in proper container/bottle? Yes  No

Sample containers intact? Yes  No

Sufficient sample volume for indicated test? Yes  No

All samples received within holding time? Yes  No

Was TAT marked on the COC? Yes  No

Proceed with Standard TAT as per project history? Yes  No  Not Applicable

Water - VOA vials have zero headspace? No VOA vials submitted  Yes  No

Water - pH acceptable upon receipt? Yes  No  Not Applicable

Adjusted? \_\_\_\_\_ Checked by KF

Sample Condition: Good  Other(Explain) \_\_\_\_\_

(For diffusive samples or AIHA lead) Is a known blank included? Yes  No

See Case Narrative for resolution of the Non-Conformance.

\* Samples do not have to comply with the given range for certain parameters.

**Client:** Ranger Consulting  
**Project Name:** Sun Valley Dr Ext  
**Lab Order:** 1504627

**Dates Report**

Lab Sample ID	Client Sample ID	Collection Date	Matrix	Test Name	TCLP Date	Prep Date	Analysis Date
1504627-001A	SW-1	4/8/2015 12:40:00PM		Surface Water Resistivity			04/13/2015
1504627-001A	SW-1	4/8/2015 12:40:00PM		Surface Water Hydrogen Ion (pH) by SM4500 H+ B			04/10/2015

Client: Ranger Consulting  
 Project Name: Sun Valley Dr Ext  
 Workorder: 1504627

**ANALYTICAL QC SUMMARY REPORT**

BatchID: R289596

Sample ID: <b>LCS-R289596</b>	Client ID:	Units: <b>pH Units</b>	Prep Date:	Run No: <b>289596</b>							
SampleType: <b>LCS</b>	TestCode: <b>Hydrogen Ion (pH) by SM4500 H+ B</b>	BatchID: <b>R289596</b>	Analysis Date: <b>04/10/2015</b>	Seq No: <b>6156538</b>							
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

pH 7.000 0.0100 7.000 100 90 110

Sample ID: <b>1504656-001ADUP</b>	Client ID:	Units: <b>pH Units</b>	Prep Date:	Run No: <b>289596</b>							
SampleType: <b>DUP</b>	TestCode: <b>Hydrogen Ion (pH) by SM4500 H+ B</b>	BatchID: <b>R289596</b>	Analysis Date: <b>04/10/2015</b>	Seq No: <b>6156568</b>							
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

pH 6.550 0.0100 6.530 0.306 20 H

Sample ID: <b>1504674-001ADUP</b>	Client ID:	Units: <b>pH Units</b>	Prep Date:	Run No: <b>289596</b>							
SampleType: <b>DUP</b>	TestCode: <b>Hydrogen Ion (pH) by SM4500 H+ B</b>	BatchID: <b>R289596</b>	Analysis Date: <b>04/10/2015</b>	Seq No: <b>6156560</b>							
Analyte	Result	RPT Limit	SPK value	SPK Ref Val	%REC	Low Limit	High Limit	RPD Ref Val	%RPD	RPD Limit	Qual

pH 8.140 0.0100 8.130 0.123 20 H

<b>Qualifiers:</b>	> Greater than Result value	< Less than Result value	B Analyte detected in the associated method blank
	BRL Below reporting limit	E Estimated (value above quantitation range)	H Holding times for preparation or analysis exceeded
	J Estimated value detected below Reporting Limit	N Analyte not NELAC certified	R RPD outside limits due to matrix
	Rpt Lim Reporting Limit	S Spike Recovery outside limits due to matrix	

